
UnideskSDK Documentation

Ryan Butler

Dec 13, 2022

Getting Started

1	Install and Update	3
1.1	Install Manually	3
1.2	Install PSGallery	3
1.3	Update PSGallery	3
2	Changelog	5
3	Add-ALAppAssignment	7
4	Add-ALELAppassignment	9
5	Connect-ALsession	11
6	Disconnect-ALsession	13
7	Export-ALLayerRev	15
8	Get-ALapplayer	17
9	Get-ALapplayerDetail	19
10	Get-ALAuditInfo	21
11	Get-ALCachePointInfo	23
12	Get-ALconnector	25
13	Get-ALconnectoragent	27
14	Get-ALConnectorDetail	29
15	Get-ALconnectortype	31
16	Get-ALDirectory	33
17	Get-ALDirectoryDetail	35
18	Get-ALExportableRev	37

19	Get-ALicon	39
20	Get-ALiconassoc	41
21	Get-ALimage	43
22	Get-ALImageComp	45
23	Get-ALImageDetail	47
24	Get-ALImportableRev	49
25	Get-ALLayerInstallDisk	51
26	Get-ALLdapObject	53
27	Get-ALLocalUser	55
28	Get-ALOsLayer	57
29	Get-ALOsLayerDetail	59
30	Get-ALPendingOp	61
31	Get-ALPlatformlayer	63
32	Get-ALPlatformLayerDetail	65
33	Get-ALRemoteshare	67
34	Get-ALStatus	69
35	Get-ALSystemInfo	71
36	Get-ALSystemSettingInfo	73
37	Get-ALUserAssignment	75
38	Get-ALUserDetail	77
39	Get-ALUserGroupMembership	79
40	Get-ALUserList	81
41	Get-ALVcenterConnector	83
42	Get-alVcenterObject	85
43	Get-ALVMName	87
44	Import-ALLayerRev	89
45	Import-ALOsLayer	91
46	Invoke-ALCreateBundle	93
47	Invoke-ALLayerFinalize	95
48	Invoke-ALPublish	97

49	New-ALAppLayer	99
50	New-ALApplayerClone	101
51	New-ALAppLayerRev	103
52	new-aldirectory	105
53	new-ALicon	107
54	New-ALImage	109
55	New-ALImageClone	111
56	New-ALOsLayerRev	113
57	New-ALPlatformLayer	115
58	New-ALPlatformLayerRev	117
59	new-ALVcenterConnector	119
60	Remove-ALAppassignment	121
61	Remove-ALAppLayerRev	123
62	Remove-ALConnector	125
63	remove-ALDirectory	127
64	Remove-ALELAppassignment	129
65	remove-ALicon	131
66	Remove-ALImage	133
67	Remove-ALOSLayerRev	135
68	Remove-ALPlatformLayerRev	137
69	Set-ALAdminUser	139
70	Set-ALApplayer	141
71	Set-ALApplayerRev	143
72	Set-ALConnectorCred	145
73	set-aldirectory	147
74	Set-ALImage	149
75	Set-ALPlatformlayer	151
76	Set-alVcenterConnector	153
77	Stop-ALWorkTicket	155
78	test-aldirectory	157

79 test-aldirectoryauth	159
80 test-aldirectorydn	161
81 Application Assignments	163
81.1 Add app layers to an image	163
81.2 Remove app layers from an image	163
81.3 Add user\group to Elastic Layers	163
81.4 Remove user\group from Elastic Layers	164
82 Application Layers	165
82.1 New Application Layer	165
82.2 New Application Layer Version	165
82.3 Set Application Layer	166
82.4 Remove Application Layer Revision	166
83 Connect and Disconnect	167
83.1 Connect	167
83.2 Disconnect	167
84 Connectors	169
84.1 General	169
84.2 vCenter	170
85 Directory Junction	173
85.1 New Directory Junction	173
85.2 Get ALL Directory Junctions	173
85.3 Get Directory Junction Info	173
85.4 Set Directory Junction Info	173
85.5 Delete Directory Junction	174
85.6 User Info	174
86 Export and Import Layers	175
86.1 Export Layers	175
86.2 Import Layers	176
87 Icons	177
87.1 Get icon ids	177
87.2 Export all icons (save as png)	177
87.3 Get icon associations	177
87.4 Create new icon	177
87.5 Remove icon	178
88 Images	179
88.1 Get Image Composition	179
88.2 Create New Image	179
88.3 Edit Image	180
88.4 Remove Image	180
88.5 Publish Image	181
88.6 Clone Image	181
89 Local Users	183
89.1 Get Local Users	183
89.2 Set Local Admin Password	183

90	Operating System Layers	185
90.1	Import Operating System	185
90.2	New Operating System Layer Version	186
90.3	Remove Operating System Layer Revision	186
91	Platform Layers	187
91.1	New Platform Layer	187
91.2	New Platform Layer Version	187
91.3	Remove Platform Layer Revision	188
92	System Info	189
92.1	Get System Information (Version)	189
92.2	Get System Settings	189
93	Task Status	191
93.1	Get Task Status	191
93.2	Cancel Task	191

This is a reversed engineered SDK that emulates the SOAP calls that AL uses to manage the appliance. Currently only supports version **4.11 or later**. **THIS USES UNSUPPORTED API CALLS. PLEASE USE WITH CAUTION.**

CHAPTER 1

Install and Update

1.1 Install Manually

```
Import-Module ".\ctxal-sdk.psm1"
```

1.2 Install PSGallery

```
Find-Module -name ctxal-sdk  
Install-Module -Name ctxal-sdk -Scope CurrentUser
```

1.3 Update PSGallery

```
Find-Module -name ctxal-sdk  
Update-Module -Name ctxal-sdk
```

“

CHAPTER 2

Changelog

- 06-01-2018 BETA release
- 06-03-2018 Function for appliance details
- 06-03-2018 Fix in Get-almvname for message text
- 06-04-2018 Get system info functions
- 06-09-2018 Better response output and clarify examples
- 06-20-2018 Get-ALImageComp function add
- 10-05-2018 Add stop-alworkticket function
- 10-18-2018 Add XenServer OS import option (now vcenter and xenserver)
- 10-18-2018 More detail for Get-ALImageComp
- 10-30-2018 Added functionality to export, view, create, check associations and remove icons
- 11-08-2018 Added functionality to export and import layers to and from network shares
- 11-10-2018 Cleaned up parameters and better get status returns
- 12-29-2018 Added functionality for directory junctions
- 01-22-2019 Added functionality to pull user information and assignments
- 01-22-2019 Much better regex for Get-ALVMName (Thanks Bill Nickerson @wnickerson78)
- 01-29-2019 Added ability to remove layer revisions (Thanks Siebrand Feenstra @Siebrandf)
- 02-18-2019 Added better functionality to see app assignments (See ExamplesGetUserAppAssignments)
- 02-21-2019 vCenter Connector commands
- 04-01-2019 Set admin password functionality. Get local accounts
- 04-11-2019 Get connector detail and set connector credentials

Commands

This page contains details on *** commands.

Add-ALAppAssignment

NAME Add-ALAppAssignment

SYNOPSIS Adds a layer(application) assignment to image(template)

SYNTAX Add-ALAppAssignment [-websession] <Object> [-apprevId] <String> [-imageId] <String> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Adds a layer(application) assignment to image(template)

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-apprevId <String> Application layer version to be added

-imageId <String> Image or template where application should be added

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$image = Get-ALImage -websession $websession|where{$_name -eq "Accounting"}
```

```
$app = Get-ALaplayer -websession $websession|where{$_name -eq "Libre Office"} $ap-
prevs = get-alaplayerDetail -websession $websession -id $app.Id $apprevId = $ap-
prevs.Revisions.AppLayerRevisionDetail|where{$_state -eq "Deployable"}|Sort-Object revision -
Descending|select -First 1 add-alappassignment -websession $websession -apprevId $apprevId.id -imageId
$image.id
```

REMARKS To see the examples, type: “get-help Add-ALAppAssignment -examples”. For more information, type: “get-help Add-ALAppAssignment -detailed”. For technical information, type: “get-help Add-ALAppAssignment -full”.

Add-ALELAppassignment

NAME Add-ALELAppassignment

SYNOPSIS Adds a user account or group to an applications elastic layer assignment

SYNTAX Add-ALELAppassignment [-websession] <Object> [-apprevid] <String> [-unideskid] <Int64> [-directoryjunctionid] <Int64> [-ldapguid] <String> [-ldapdn] <String> [-sid] <String> [-objecttype] <String> [[-imageid] <Int64>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Adds a user account or group to an applications elastic layer assignment

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-apprevid <String> Application version layer ID

-unideskid <Int64>

-directoryjunctionid <Int64>

-ldapguid <String>

-ldapdn <String>

-sid <String>

-objecttype <String>

-imageid <Int64>

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>\$user = get-alldapobject -websession \$websession -object "myusername"

```
add-alelappassignment -websession $websession -apprevId $apprevId.Id -unideskid $unideskid -objecttype $objecttype -directoryjunctionid $directoryjunctionid -ldapguid $ldapguid -ldapdn $ldapdn -sid $sid -Confirm:$False
```

EXAMPLE 2

```
PS C:>$users = @('MyGroup1','MyGroup2','Domain Users')
```

```
$finduser = $users|get-alldapobject -websession $websession $app = Get-ALaplayerDetail -websession $web-session|where{$_name -eq "Libre Office"} $apprevs = Get-ALaplayerDetail -websession $websession -id $app.Id $apprevId = $apprevs.Revisions.AppLayerRevisionDetail|where{$_state -eq "Deployable"}|Sort-Object revision -Descending|select -First 1 add-alelappassignment -websession $websession -apprevId $apprevId.Id -unideskid $finduser.unideskid -objecttype $finduser.objecttype -directoryjunctionid $find-user.directoryjunctionid -ldapguid $finduser.guid -ldapdn $finduser.dn -sid $finduser.sid -Confirm:$False
```

REMARKS To see the examples, type: “get-help Add-ALELAppassignment -examples”. For more information, type: “get-help Add-ALELAppassignment -detailed”. For technical information, type: “get-help Add-ALELAppassignment -full”.

Commands

This page contains details on *** commands.

Connect-ALsession

NAME Connect-ALsession

SYNOPSIS Connects to the Citrix Application Layering appliance and creates a web request session

SYNTAX Connect-ALsession [-Credential] <PSCredential> [-aplip] <String> [<CommonParameters>]

DESCRIPTION Connects to the Citrix Application Layering appliance and creates a web request session

PARAMETERS

-Credential <PSCredential> PowerShell credential object

-aplip <String>

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>\$websession = Connect-alsession -aplip \$aplip -Credential \$Credential -Verbose

REMARKS To see the examples, type: “get-help Connect-ALsession -examples”. For more information, type: “get-help Connect-ALsession -detailed”. For technical information, type: “get-help Connect-ALsession -full”.

Commands

This page contains details on *** commands.

Disconnect-ALsession

NAME Disconnect-ALsession

SYNOPSIS Logs off and disconnects web session

SYNTAX Disconnect-ALsession [-websession] <Object> [<CommonParameters>]

DESCRIPTION Logs off and disconnects web session

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Disconnect-ALsession -websession $websession
```

REMARKS To see the examples, type: “get-help Disconnect-ALsession -examples”. For more information, type: “get-help Disconnect-ALsession -detailed”. For technical information, type: “get-help Disconnect-ALsession -full”.

Commands

This page contains details on *** commands.

Export-ALLayerRev

NAME Export-ALLayerRev

SYNOPSIS Gets revisions that can be used to export

SYNTAX Export-ALLayerRev [-websession] <Object> [-sharepath] <String> [-id] <String> [[-username] <String>] [[-sharepw] <String>] [<CommonParameters>]

DESCRIPTION Gets revisions that can be used to export

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-sharepath <String> Share UNC Path type

-id <String> ID(s) of revision layers to export

-username <String> Share username

-sharepw <String> Share password

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Export-ALLayerrev -websession $websession -sharepath "\\myserverpathlayers" -id
@(12042,225252,2412412)
```

REMARKS To see the examples, type: “get-help Export-ALLayerRev -examples”. For more information, type: “get-help Export-ALLayerRev -detailed”. For technical information, type: “get-help Export-ALLayerRev -full”.

Commands

This page contains details on *** commands.

Get-ALapplayer

NAME Get-ALapplayer

SYNOPSIS Gets all application layers

SYNTAX Get-ALapplayer [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets all application layers

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALapplayer -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALapplayer -examples”. For more information, type: “get-help Get-ALapplayer -detailed”. For technical information, type: “get-help Get-ALapplayer -full”.

Get-ALapplayerDetail

NAME Get-ALapplayerDetail

SYNOPSIS Gets detailed information on Application Layer including revisions(versions)

SYNTAX Get-ALapplayerDetail [-websession] <Object> [-id] <String> [<CommonParameters>]

DESCRIPTION Gets detailed information on Application Layer including revisions(versions)

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Application layer ID

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>get-alaplayer -websession $websession -id $app.Id
```

REMARKS To see the examples, type: “get-help Get-ALapplayerDetail -examples”. For more information, type: “get-help Get-ALapplayerDetail -detailed”. For technical information, type: “get-help Get-ALapplayerDetail -full”.

CHAPTER 10

Get-ALAuditInfo

NAME Get-ALAuditInfo

SYNOPSIS Gets audit information

SYNTAX Get-ALAuditInfo [-websession] <Object> [-entitytype] <String> [[-id] <String>] [<CommonParameters>]

DESCRIPTION Gets System Settings

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-entitytype <String> Type of log to pull

-id <String> ID of entity to pull audit logs

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Get-ALAuditInfo -websession $websession -entitytype OsLayer -id 753664
```

EXAMPLE 2

```
PS C:>Get-ALAuditInfo -websession $websession -entitytype ManagementAppliance
```

REMARKS To see the examples, type: “get-help Get-ALAuditInfo -examples”. For more information, type: “get-help Get-ALAuditInfo -detailed”. For technical information, type: “get-help Get-ALAuditInfo -full”.

Get-ALCachePointInfo

NAME Get-ALCachePointInfo

SYNOPSIS Gets appliance Layering Service Info

SYNTAX Get-ALCachePointInfo [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets appliance Layering Service Info

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALCachePointInfo -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALCachePointInfo -examples”. For more information, type: “get-help Get-ALCachePointInfo -detailed”. For technical information, type: “get-help Get-ALCachePointInfo -full”.

CHAPTER 12

Get-ALconnector

NAME Get-ALconnector

SYNOPSIS Gets all appliance connectors currently configured

SYNTAX Get-ALconnector [-websession] <Object> [-type] <String> [[-name] <String>] [<CommonParameters>]

DESCRIPTION Gets all appliance connectors currently configured

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-type <String> Connector type for publishing or creating layersimages

-name <String> Name of object to return

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALconnector -websession \$websession -type "Publish"

REMARKS To see the examples, type: "get-help Get-ALconnector -examples". For more information, type: "get-help Get-ALconnector -detailed". For technical information, type: "get-help Get-ALconnector -full".

Get-ALconnectoragent

NAME Get-ALconnectoragent

SYNOPSIS Gets connector agents

SYNTAX Get-ALconnectoragent [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets connector agents

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALconnectoragent -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALconnectoragent -examples”. For more information, type: “get-help Get-ALconnectoragent -detailed”. For technical information, type: “get-help Get-ALconnectoragent -full”.

Get-ALConnectorDetail

NAME Get-ALConnectorDetail

SYNOPSIS Gets Detailed Connector configurations

SYNTAX Get-ALConnectorDetail [-websession] <Object> [[-name] <String>] [-includescripts] [[-port] <String>] [[-connid] <String>] [<CommonParameters>]

DESCRIPTION Gets Detailed Connector configurations

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-name <String>

-includescripts [<SwitchParameter>] Include ELM script hosts in return

-port <String> port of the specific connector (Use: Get-ALConnector)

-connid <String> connection ID of the specific connector (Use: Get-ALConnector)

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>get-alconnectordetail -websession $websession -connid $connector.Id -port $connector.ConfigurationSslPort
```

REMARKS To see the examples, type: “get-help Get-ALConnectorDetail -examples”. For more information, type: “get-help Get-ALConnectorDetail -detailed”. For technical information, type: “get-help Get-ALConnectorDetail -full”.

Get-ALconnectortype

NAME Get-ALconnectortype

SYNOPSIS Gets all Connector Types

SYNTAX Get-ALconnectortype [-websession] <Object> [[-name] <String>] [<CommonParameters>]

DESCRIPTION Gets all Connector Types

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-name <String> Name of object to return

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

REMARKS To see the examples, type: “get-help Get-ALconnectortype -examples”. For more information, type: “get-help Get-ALconnectortype -detailed”. For technical information, type: “get-help Get-ALconnectortype -full”.

CHAPTER 16

Get-ALDirectory

NAME Get-ALDirectory

SYNOPSIS Gets Directory Junctions

SYNTAX Get-ALDirectory [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets Directory Junctions

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALDirectory -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALDirectory -examples”. For more information, type: “get-help Get-ALDirectory -detailed”. For technical information, type: “get-help Get-ALDirectory -full”.

Get-ALDirectoryDetail

NAME Get-ALDirectoryDetail

SYNOPSIS Gets additional directory junction detail

SYNTAX Get-ALDirectoryDetail [-websession] <Object> [-id] <String> [<CommonParameters>]

DESCRIPTION Gets additional directory junction detail

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Directory Junction id

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>get-aldirectorydetail -websession \$websession -id \$directory.id

REMARKS To see the examples, type: “get-help Get-ALDirectoryDetail -examples”. For more information, type: “get-help Get-ALDirectoryDetail -detailed”. For technical information, type: “get-help Get-ALDirectoryDetail -full”.

Get-ALExportableRev

NAME Get-ALExportableRev

SYNOPSIS Gets revisions that can be used to export to share

SYNTAX Get-ALExportableRev [-websession] <Object> [-sharepath] <String> [[-username] <String>] [[-sharepw] <String>] [-showall] [<CommonParameters>]

DESCRIPTION Gets revisions that can be used to export to share

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-sharepath <String> Share UNC Path type

-username <String> Share username

-sharepw <String> Share password

-showall [<SwitchParameter>] Get all layers including non exportable ones

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALExportableRev -websession \$websession -sharepath "\\myserverpathlayers"

REMARKS To see the examples, type: "get-help Get-ALExportableRev -examples". For more information, type: "get-help Get-ALExportableRev -detailed". For technical information, type: "get-help Get-ALExportableRev -full".

NAME Get-ALicon

SYNOPSIS Gets all icon IDs

SYNTAX Get-ALicon [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets all icon IDs

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Get-ALicon -websession $websession
```

REMARKS To see the examples, type: “get-help Get-ALicon -examples”. For more information, type: “get-help Get-ALicon -detailed”. For technical information, type: “get-help Get-ALicon -full”.

CHAPTER 20

Get-ALIconassoc

NAME Get-ALIconassoc

SYNOPSIS Gets items associated with icon

SYNTAX Get-ALIconassoc [-websession] <Object> [-iconid] <String> [<CommonParameters>]

DESCRIPTION Gets items associated with icon

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-iconid <String> Icon ID

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

————— EXAMPLE 1 —————

PS C:>Get-ALIcon -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALIconassoc -examples”. For more information, type: “get-help Get-ALIconassoc -detailed”. For technical information, type: “get-help Get-ALIconassoc -full”.

Get-ALImage

NAME Get-ALImage

SYNOPSIS Gets all images(templates)

SYNTAX Get-ALImage [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets all images(templates)

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Get-ALImage -websession $websession
```

REMARKS To see the examples, type: “get-help Get-ALImage -examples”. For more information, type: “get-help Get-ALImage -detailed”. For technical information, type: “get-help Get-ALImage -full”.

Get-ALImageComp

NAME Get-ALImageComp

SYNOPSIS Gets image composition details

SYNTAX Get-ALImageComp [-websession] <Object> [[-id] <String>] [[-name] <String>] [<CommonParameters>]

DESCRIPTION Gets image composition details

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Image(template) id

-name <String> Image name (supports wildcard)

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

————— EXAMPLE 1 —————

PS C:>Gets all images and layer composition

Get-ALImageComp -websession \$websession

————— EXAMPLE 2 —————

PS C:>Gets image and layer composition based on ID

Get-ALImageComp -websession \$websession -id 5535

————— EXAMPLE 3 —————

PS C:>Gets image and layer composition based on name

Get-ALImageComp -websession \$websession -name "Windows 10"

————— EXAMPLE 4 —————

PS C:>Gets image and layer composition based on name (wildcard)

Get-ALImageComp -websession \$websession -name “10”

REMARKS To see the examples, type: “get-help Get-ALImageComp -examples”. For more information, type: “get-help Get-ALImageComp -detailed”. For technical information, type: “get-help Get-ALImageComp -full”.

Get-ALImageDetail

NAME Get-ALImageDetail

SYNOPSIS Gets additional image(template) detail

SYNTAX Get-ALImageDetail [-websession] <Object> [-id] <String> [<CommonParameters>]

DESCRIPTION Gets additional image(template) detail

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Image(template) id

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>get-alimagedetail -websession $websession -id $image.id
```

REMARKS To see the examples, type: “get-help Get-ALImageDetail -examples”. For more information, type: “get-help Get-ALImageDetail -detailed”. For technical information, type: “get-help Get-ALImageDetail -full”.

Get-ALImportableRev

NAME Get-ALImportableRev

SYNOPSIS Gets revisions that can be used to import

SYNTAX Get-ALImportableRev [-websession] <Object> [-sharepath] <String> [[-username] <String>] [[-sharepw] <String>] [-showall] [<CommonParameters>]

DESCRIPTION Gets revisions that can be used to import

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-sharepath <String> Share UNC Path type

-username <String> Share username

-sharepw <String> Share password

-showall [<SwitchParameter>] Get all layers including non exportable ones

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALImportableRev -websession \$websession -sharepath "\\myserverpathlayers"

REMARKS To see the examples, type: "get-help Get-ALImportableRev -examples". For more information, type: "get-help Get-ALImportableRev -detailed". For technical information, type: "get-help Get-ALImportableRev -full".

Get-ALLayerInstallDisk

NAME Get-ALLayerInstallDisk

SYNOPSIS Gets install disk location during finalize process

SYNTAX Get-ALLayerInstallDisk [-websession] <Object> [-id] <String> [<CommonParameters>]

DESCRIPTION Gets install disk location during finalize process

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Layer ID to be located

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>get-allayerinstalldisk -websession \$websession -layerid \$apprevid.LayerId

REMARKS To see the examples, type: “get-help Get-ALLayerInstallDisk -examples”. For more information, type: “get-help Get-ALLayerInstallDisk -detailed”. For technical information, type: “get-help Get-ALLayerInstallDisk -full”.

Get-ALLdapObject

NAME Get-ALLdapObject

SYNOPSIS Locates LDAP user or group object

SYNTAX Get-ALLdapObject [-websession] <Object> [-object] <String> [<CommonParameters>]

DESCRIPTION Locates LDAP user or group object

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-object <String> Group or user to be located

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

————— EXAMPLE 1 —————

```
PS C:>get-alldapobject -websession $websession -object "myusername"
```

————— EXAMPLE 2 —————

```
PS C:>$users = @('MyGroup1','MyGroup2','Domain Users')
```

```
$finduser = $users|get-alldapobject -websession $websession
```

REMARKS To see the examples, type: “get-help Get-ALLdapObject -examples”. For more information, type: “get-help Get-ALLdapObject -detailed”. For technical information, type: “get-help Get-ALLdapObject -full”.

Get-ALLocalUser

NAME Get-ALLocalUser

SYNOPSIS Gets ELM local users

SYNTAX Get-ALLocalUser [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets ELM local users

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALLocalUser -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALLocalUser -examples”. For more information, type: “get-help Get-ALLocalUser -detailed”. For technical information, type: “get-help Get-ALLocalUser -full”.

Get-ALOsLayer

NAME Get-ALOsLayer

SYNOPSIS Gets all OS layers

SYNTAX Get-ALOsLayer [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets all OS layers

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALOsLayer -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALOsLayer -examples”. For more information, type: “get-help Get-ALOsLayer -detailed”. For technical information, type: “get-help Get-ALOsLayer -full”.

Get-ALOsLayerDetail

NAME Get-ALOsLayerDetail

SYNOPSIS Gets detailed information on a OS layer including revisions

SYNTAX Get-ALOsLayerDetail [-websession] <Object> [-id] <String> [<CommonParameters>]

DESCRIPTION Gets detailed information on a OS layer including revisions

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Operating System Layer ID

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>get-aloslayerdetail -websession \$websession -id \$app.AssociatedOsLayerId

REMARKS To see the examples, type: “get-help Get-ALOsLayerDetail -examples”. For more information, type: “get-help Get-ALOsLayerDetail -detailed”. For technical information, type: “get-help Get-ALOsLayerDetail -full”.

CHAPTER 30

Get-ALPendingOp

NAME Get-ALPendingOp

SYNOPSIS Gets appliance operation based on ID

SYNTAX Get-ALPendingOp [-websession] <Object> [-id] <String> [<CommonParameters>]

DESCRIPTION Gets appliance operation based on ID

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> workticket id

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALPendingOp -websession \$websession -id \$myworkid

REMARKS To see the examples, type: “get-help Get-ALPendingOp -examples”. For more information, type: “get-help Get-ALPendingOp -detailed”. For technical information, type: “get-help Get-ALPendingOp -full”.

Get-ALPlatformlayer

NAME Get-ALPlatformlayer

SYNOPSIS Gets all platform layers

SYNTAX Get-ALPlatformlayer [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets all platform layers

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALPlatformlayer -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALPlatformlayer -examples”. For more information, type: “get-help Get-ALPlatformlayer -detailed”. For technical information, type: “get-help Get-ALPlatformlayer -full”.

Get-ALPlatformLayerDetail

NAME Get-ALPlatformLayerDetail

SYNOPSIS Gets detailed information on a platform layer including revisions

SYNTAX Get-ALPlatformLayerDetail [-websession] <Object> [-id] <String> [<CommonParameters>]

DESCRIPTION Gets detailed information on a platform layer including revisions

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Platform layer ID

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>get-alplatformlayerDetail -websession \$websession -id \$platform.id

REMARKS To see the examples, type: “get-help Get-ALPlatformLayerDetail -examples”. For more information, type: “get-help Get-ALPlatformLayerDetail -detailed”. For technical information, type: “get-help Get-ALPlatformLayerDetail -full”.

Get-ALRemoteshare

NAME Get-ALRemoteshare

SYNOPSIS Gets CIFS share information currently configured

SYNTAX Get-ALRemoteshare [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets CIFS share information currently configured

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALRemoteshare -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALRemoteshare -examples”. For more information, type: “get-help Get-ALRemoteshare -detailed”. For technical information, type: “get-help Get-ALRemoteshare -full”.

Get-ALStatus

NAME Get-ALStatus

SYNOPSIS Gets any non-completed task currently running on appliance

SYNTAX Get-ALStatus [-websession] <Object> [[-id] <String>] [<CommonParameters>]

DESCRIPTION Gets any non-completed task currently running on appliance

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Workticket ID of job

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

————— EXAMPLE 1 —————

PS C:>Get-ALStatus -websession \$websession

————— EXAMPLE 2 —————

PS C:>Get-ALStatus -websession \$websession -id "4521984"

REMARKS To see the examples, type: “get-help Get-ALStatus -examples”. For more information, type: “get-help Get-ALStatus -detailed”. For technical information, type: “get-help Get-ALStatus -full”.

Get-ALSystemInfo

NAME Get-ALSystemInfo

SYNOPSIS Gets appliance System Details

SYNTAX Get-ALSystemInfo [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets appliance System Details

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALSystemInfo -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALSystemInfo -examples”. For more information, type: “get-help Get-ALSystemInfo -detailed”. For technical information, type: “get-help Get-ALSystemInfo -full”.

Get-ALSystemSettingInfo

NAME Get-ALSystemSettingInfo

SYNOPSIS Gets appliance System Settings

SYNTAX Get-ALSystemSettingInfo [-websession] <Object> [<CommonParameters>]

DESCRIPTION Gets appliance System Settings

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALSystemSettingInfo -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALSystemSettingInfo -examples”. For more information, type: “get-help Get-ALSystemSettingInfo -detailed”. For technical information, type: “get-help Get-ALSystemSettingInfo -full”.

Get-ALUserAssignment

NAME Get-ALUserAssignment

SYNOPSIS Gets user app layer assignments

SYNTAX Get-ALUserAssignment [-websession] <Object> [-id] <String[]> [<CommonParameters>]

DESCRIPTION Gets user app layer assignments

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String[]> Unidesk ID of user

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALUserAssignments -websession \$websession -id "4521984" -Verbose

REMARKS To see the examples, type: “get-help Get-ALUserAssignment -examples”. For more information, type: “get-help Get-ALUserAssignment -detailed”. For technical information, type: “get-help Get-ALUserAssignment -full”.

Get-ALUserDetail

NAME Get-ALUserDetail

SYNOPSIS Gets detailed information on user from directory junction

SYNTAX Get-ALUserDetail [-websession] <Object> [-id] <String> [-junctionid] <String> [-ldapguid] <String> [-dn] <String> [<CommonParameters>]

DESCRIPTION Gets detailed information on user from directory junction

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Unidesk ID of user

-junctionid <String> Directory junction ID

-ldapguid <String>

-dn <String> LDAP DN of user

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Get-ALUserDetail -websession $websession -junctionid $dir.id -ldapguid $userid.DirectoryId.LdapGuid
-dn $userid.DirectoryId.LdapDN -id $userid.DirectoryId.UnideskId
```

REMARKS To see the examples, type: “get-help Get-ALUserDetail -examples”. For more information, type: “get-help Get-ALUserDetail -detailed”. For technical information, type: “get-help Get-ALUserDetail -full”.

Get-ALUserGroupMembership

NAME Get-ALUserGroupMembership

SYNOPSIS Gets group membership of user

SYNTAX Get-ALUserGroupMembership [-websession] <Object> [-id] <String> [-junctionid] <String> [-ldapguid] <String> [-ldapdn] <String> [-sid] <String> [<CommonParameters>]

DESCRIPTION Gets group membership of user

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Unidesk ID of user

-junctionid <String> Directory Junction ID

-ldapguid <String> User LDAP guid

-ldapdn <String> User LDAP DN

-sid <String> User SID

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Get-ALUserGroupMembership -websession $websession -junctionid $dir.id -id
$User.DirectoryId.UnideskId -ldapguid $user.FullId.LdapGuid -ldapdn $user.FullId.LdapDN -sid $userde-
tail.FullId.sid
```

REMARKS To see the examples, type: “get-help Get-ALUserGroupMembership -examples”. For more information, type: “get-help Get-ALUserGroupMembership -detailed”. For technical information, type: “get-help Get-ALUserGroupMembership -full”.

CHAPTER 40

Get-ALUserList

NAME Get-ALUserList

SYNOPSIS Gets list of users and groups for specific LDAP DN

SYNTAX Get-ALUserList [-websession] <Object> [-junctionid] <String> [[-dn] <String>] [<CommonParameters>]

DESCRIPTION Gets list of users and groups for specific LDAP DN

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-junctionid <String> Directory junction ID

-dn <String> LDAP DN of user location

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Get-ALUserList -websession $websession -junctionid $dir.id -dn "CN=Users,DC=mydomain,DC=com"
```

EXAMPLE 2

```
PS C:>Get-ALUserList -websession $websession -junctionid $dir.id
```

REMARKS To see the examples, type: “get-help Get-ALUserList -examples”. For more information, type: “get-help Get-ALUserList -detailed”. For technical information, type: “get-help Get-ALUserList -full”.

Get-ALVcenterConnector

NAME Get-ALVcenterConnector

SYNOPSIS Gets Vcenter Connector configuration

SYNTAX Get-ALVcenterConnector [-websession] <Object> [[-name] <String>] [-includescripts] [[-connid] <String>] [<CommonParameters>]

DESCRIPTION Gets Vcenter Connector configuration

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-name <String> Name of object to return

-includescripts [<SwitchParameter>] Include ELM script hosts in return

-connid <String>

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALVcenterConnector -websession \$websession

REMARKS To see the examples, type: “get-help Get-ALVcenterConnector -examples”. For more information, type: “get-help Get-ALVcenterConnector -detailed”. For technical information, type: “get-help Get-ALVcenterConnector -full”.

Get-alVcenterObject

NAME Get-alVcenterObject

SYNOPSIS Gets Vcenter Connector datacenters

SYNTAX Get-alVcenterObject [-websession] <Object> [[-configid] <String>] [-vcenter] <String> [[-vcenterpass] <String>] [-username] <String> [-type] <String> [[-dc] <String>] [[-vmfolder] <String>] [[-name] <String>] [<CommonParameters>]

DESCRIPTION Gets Vcenter Connector datacenters

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-configid <String> Connector ID

-vcenter <String> vCenter Hostname

-vcenterpass <String> Password to authenticate to vcenter

-username <String> Username to authenticate to vcenter

-type <String> Type of object to return

-dc <String> vCenter Datacenter ID to query

-vmfolder <String> vCenter folder ID to query

-name <String> Name of object to return

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-alVcenterObjectDataCenter -websession \$websession -configid \$vcenter.pccId -username \$vcenter.pccConfig.userName -vcenter \$vcenter.pccConfig.vCenterServer -Verbose

REMARKS To see the examples, type: “get-help Get-alVcenterObject -examples”. For more information, type: “get-help Get-alVcenterObject -detailed”. For technical information, type: “get-help Get-alVcenterObject -full”.

Get-ALVMName

NAME Get-ALVMName

SYNOPSIS Extracts VM name out of “action required” task

SYNTAX Get-ALVMName [-message] <Object> [<CommonParameters>]

DESCRIPTION Extracts VM name out of “action required” task

PARAMETERS

-message <Object> Message from pending operation

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Get-ALVMName -message \$status.WorkItems.WorkItemResult.Status

REMARKS To see the examples, type: “get-help Get-ALVMName -examples”. For more information, type: “get-help Get-ALVMName -detailed”. For technical information, type: “get-help Get-ALVMName -full”.

Commands

This page contains details on *** commands.

CHAPTER 44

Import-ALLayerRev

NAME Import-ALLayerRev

SYNOPSIS Imports existing layers from share into ELM

SYNTAX Import-ALLayerRev [-websession] <Object> [-sharepath] <String> [-id] <String> [[-username] <String>] [[-sharepw] <String>] [<CommonParameters>]

DESCRIPTION Imports existing layers from share into ELM

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-sharepath <String> Share UNC Path type

-id <String> ID(s) of revision layers to export

-username <String> Share username

-sharepw <String> Share password

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Import-ALLayerrevs -websession $websession -sharepath "\\myserverpathlayers" -id
@(12042,225252,2412412)
```

REMARKS To see the examples, type: “get-help Import-ALLayerRev -examples”. For more information, type: “get-help Import-ALLayerRev -detailed”. For technical information, type: “get-help Import-ALLayerRev -full”.

Import-ALOsLayer

NAME Import-ALOsLayer

SYNOPSIS Creates a new operating system layer

SYNTAX Import-ALOsLayer [-websession] <Object> [-vmname] <String> [[-description] <String>] [-connectorid] <String> [-shareid] <String> [[-icon] <String>] [-name] <String> [[-size] <String>] [-version] <String> [-vmid] <String> [-hypervisor] <String[]> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates a new operating system layer

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-vmname <String> Virtual machine name to import from

-description <String> Description of the layer

-connectorid <String> ID of Connector to use

-shareid <String> ID of file share

-icon <String> Icon ID (default 196608)

-name <String> Name of the layer

-size <String> Size of layer in GB (default 61440)

-version <String> Version number of the layer

-vmid <String> Virtual Machine ID from vCenter or GUID XenCenter

-hypervisor <String[]> Hypervisor to import from (ESXI or XenServer)

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$fileshare = Get-ALRemoteshare -websession $websession

$connector = Get-ALconnector -websession $websession -type CreateIwhere{$_name -eq "MYvCenter"}
$shares = get-alremoteshare -websession $websession #vCenter Command $vm = Get-VM "Windows2016VM"
$vmid = $vm.Id -replace "VirtualMachine-","" $response = import-aloslayer -websession $websession -
vmname $vm.name -connectorid $connector.id -shareid $fileshare.id -name "Windows 2016" -version "1.0"
-vmid $vmid -hypervisor esxi
```

EXAMPLE 2

```
PS C:>$fileshare = Get-ALRemoteshare -websession $websession

$connector = Get-ALconnector -websession $websession -type CreateIwhere{$_name -eq "MYXenCenter"}
$shares = get-alremoteshare -websession $websession #Xen Command $XenVM = get-xenvm -name $VM-
Name $response = import-aloslayer -websession $websession -vmname $vmname -connectorid $connector.id
-shareid $fileshare.id -name "Windows 2016" -version "1.0" -vmid $XenVM.uuid -hypervisor xenserver
```

REMARKS To see the examples, type: “get-help Import-ALOsLayer -examples”. For more information, type: “get-help Import-ALOsLayer -detailed”. For technical information, type: “get-help Import-ALOsLayer -full”.

Commands

This page contains details on *** commands.

Invoke-ALCreateBundle

NAME Invoke-ALCreateBundle

SYNOPSIS Creates diagnostic bundle

SYNTAX Invoke-ALCreateBundle [-websession] <Object> [-IncludeCrashDumps] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates diagnostic bundle

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-IncludeCrashDumps [<SwitchParameter>]

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Invoke-ALCreateBundle -websession \$websession

REMARKS To see the examples, type: “get-help Invoke-ALCreateBundle -examples”. For more information, type: “get-help Invoke-ALCreateBundle -detailed”. For technical information, type: “get-help Invoke-ALCreateBundle -full”.

Invoke-ALLayerFinalize

NAME Invoke-ALLayerFinalize

SYNOPSIS Runs finalize process on a layer

SYNTAX Invoke-ALLayerFinalize [-websession] <Object> [-fileshareid] <String> [-LayerRevisionId] <String> [-uncpath] <String> [-filename] <String> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Runs finalize process on a layer

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-fileshareid <String> ID of file share location used to store disk

-LayerRevisionId <String> Revision ID of layer to be finalized

-uncpath <String> UNC Path of fileshare

-filename <String> Filename of the disk

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>\$app = Get-ALaplayer -websession \$websession|where{\$_name -eq "7-Zip"}

\$apprevs = get-alaplayerdetail -websession \$websession -id \$app.Id \$shares = get-alremoteshare -websession \$websession \$apprevid = \$apprevs.Revisions.AppLayerRevisionDetail|where{\$_state -eq "Finalizable"}|Sort-Object revision -Descending|select -First 1 \$disklocation = get-allayerinstalldisk -websession \$websession -layerid \$apprevid.LayerId invoke-allayerfinalize -websession \$websession -fileshareid \$shares.id -LayerRevisionId \$apprevid.Id -uncpath \$disklocation.diskuncpath -filename \$disklocation.diskname

REMARKS To see the examples, type: “get-help Invoke-ALLayerFinalize -examples”. For more information, type: “get-help Invoke-ALLayerFinalize -detailed”. For technical information, type: “get-help Invoke-ALLayerFinalize -full”.

Invoke-ALPublish

NAME Invoke-ALPublish

SYNOPSIS Publishes image(template)

SYNTAX Invoke-ALPublish [-websession] <Object> [-imageid] <Array> [[-description] <Array>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Publishes image(template)

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-imageid <Array> Image ID's to be published

-description <Array>

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$images = Get-ALImage -websession $websession|where{$_.name -eq "Win 10 Accounting"}
```

```
$image = get-alimagedetail -websession $websession -id $images.Id invoke-alpublish -websession $websession -imageid $images.id
```

REMARKS To see the examples, type: “get-help Invoke-ALPublish -examples”. For more information, type: “get-help Invoke-ALPublish -detailed”. For technical information, type: “get-help Invoke-ALPublish -full”.

Commands

This page contains details on *** commands.

New-ALAppLayer

NAME New-ALAppLayer

SYNOPSIS Creates a new application layer

SYNTAX New-ALAppLayer [-websession] <Object> [-version] <String> [-name] <String> [[-description] <String>] [[-revdescription] <String>] [[-OsLayerSwitching] <String>] [-connectorid] <String> [-osrevid] <String> [[-platformrevid] <String>] [[-appprereqid] <String[]>] [-diskformat] <String> [-fileshareid] <String> [[-size] <String>] [[-icon] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates a new application layer

PARAMETERS

- websession <Object>** Existing Webrequest session for ELM Appliance
- version <String>** Version of the layer
- name <String>** Name of the layer
- description <String>** Description of the layer
- revdescription <String>** Revision description
- OsLayerSwitching <String>** Allow OS Switching NotBoundToOsLayer=ON BoundToOsLayer=OFF
- connectorid <String>** ID of Connector to use
- osrevid <String>** Operating system version ID
- platformrevid <String>** Platform version ID if needed
- appprereqid <String[]>** Application Layer Prerequisite version ID(s) if needed
- diskformat <String>** Disk format of the image
- fileshareid <String>** Fileshare ID to store disk
- size <String>** Size of layer in GB (default 10240)
- icon <String>** Icon ID (default 196608)

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$connector = Get-ALconnector -websession $websession -type CreateIwhere{$_name -eq "MYvCenter"}
```

```
$fileshare = Get-ALRemoteshare -websession $websession $oss = Get-ALOsLayer -websession $websessionIwhere{$_name -eq "Windows 10 x64"} $osrevs = get-aloslayerDetail -websession $websession -id $oss.id $osrevid = $osrevs.Revisions.OsLayerRevisionDetailIwhere{$_state -eq "Deployable"}|Sort-Object revision -Descending|select -First 1 new-alaplayer -websession $websession -version "1.0" -name "Accounting APP" -description "Accounting application" -connectorid $connector.id -osrevid $osrevid.Id -diskformat $connector.ValidDiskFormats.DiskFormat -OsLayerSwitching BoundToOsLayer -fileshareid $fileshare.id
```

REMARKS To see the examples, type: “get-help New-ALAppLayer -examples”. For more information, type: “get-help New-ALAppLayer -detailed”. For technical information, type: “get-help New-ALAppLayer -full”.

New-ALApplayerClone

NAME New-ALApplayerClone

SYNOPSIS Clones a Layer

SYNTAX New-ALApplayerClone [-websession] <Object> [-apprevid] <Object> [-name] <String> [[-description] <String>] [[-iconid] <String>] [-targetrevversion] <String> [[-targetrevdescription] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Clones a Layer

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-apprevid <Object> Application revision version id to clone from

-name <String> Name of the cloned layer

-description <String> Description of the cloned layer

-iconid <String> Icon ID

-targetrevversion <String> Versionname of the cloned layer revision

-targetrevdescription <String> Description for the cloned layer revision

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$layer = Get-ALApplayer -websession $websession | Where-Object {$_.name -like "S2016_APP_JAVA"}
```

```
$apprevs = Get-ALApplayerDetail -websession $websession -id $layer.id $apprevid = $apprevs.Revisions.AppLayerRevisionDetail | Sort-Object id | Select-Object -Last 1 $targetrevversion =
```

```
$apprevid.DisplayedVersion $targetrevdescription = "Cloned revision $($targetrevversion)" $name =
"$($Layer.name)_Copy" $description = $($Layer.name) $Iconid = $(Get-ALicon -websession $webses-
sion | Where-Object {(Get-ALiconassoc -iconid $_.iconid -websession $websession -ea 0) | Where-Object
{$_id -match $layer.id} }).Iconid
```

REMARKS To see the examples, type: “get-help New-AIApplayerClone -examples”. For more information, type: “get-help New-AIApplayerClone -detailed”. For technical information, type: “get-help New-AIApplayerClone -full”.

New-ALAppLayerRev

NAME New-ALAppLayerRev

SYNOPSIS Creates a new layer version

SYNTAX New-ALAppLayerRev [-websession] <Object> [-version] <String> [-name] <String> [[-description] <String>] [-connectorid] <String> [-appid] <String> [-apprev] <String> [-osrev] <String> [[-platformrev] <String>] [[-appprereq] <String[]>] [-diskformat] <String> [-fileshareid] <String> [[-size] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates a new layer version

PARAMETERS

- websession <Object>** Existing Webrequest session for ELM Appliance
- version <String>** Version of the revision
- name <String>** Name of the layer revision
- description <String>** Description of the revision
- connectorid <String>** ID of Connector to use
- appid <String>**
- apprev <String>** Base application version layer id to use
- osrev <String>** OS version layer id to use
- platformrev <String>** Platform version ID if needed
- appprereq <String[]>** Application Layer Prerequisite version ID(s) if needed
- diskformat <String>** Diskformat to store layer
- fileshareid <String>**
- size <String>** Size of layer in GB (default 10240)
- WhatIf [<SwitchParameter>]**
- Confirm [<SwitchParameter>]**

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$fileshare = Get-ALRemoteshare -websession $websession
```

```
$connector = Get-ALconnector -websession $websession -type CreateIwhere{$_name -eq "MYvCenter"}
$app = Get-ALapplayer -websession $websessionIwhere{$_name -eq "7-Zip"} $oss = Get-ALOsLayer -
websession $websession $osrevs = get-aloslayerdetail -websession $websession -id $app.AssociatedOsLayerId
$osrevid = $osrevs.Revisions.OsLayerRevisionDetailIwhere{$_state -eq "Deployable"}|Sort-Object revision -
DescendingIselect -First 1 $apprevs = get-alaplayerDetail -websession $websession -id $app.Id $appre-
vid = $apprevs.Revisions.AppLayerRevisionDetailIwhere{$_state -eq "Deployable"}|Sort-Object revision -
DescendingIselect -First 1 new-alaplayerrev -websession $websession -version "9.0" -name $app.Name -
connectorid $connector.id -appid $app.Id -apprevid $apprevid.id -osrevid $osrevid.Id -diskformat $connec-
tor.ValidDiskFormats.DiskFormat -fileshareid $fileshare.id
```

REMARKS To see the examples, type: “get-help New-ALAppLayerRev -examples”. For more information, type: “get-help New-ALAppLayerRev -detailed”. For technical information, type: “get-help New-ALAppLayerRev -full”.

new-aldirectory

NAME new-aldirectory

SYNOPSIS Creates Directory Junction

SYNTAX new-aldirectory [-websession] <Object> [-name] <String> [-serveraddress] <String> [[-port] <String>] [-usessl] [-username] <String> [-adpassword] <String> [-basedn] <String> [-force] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates Directory Junction

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-name <String> Junction name

-serveraddress <String> AD server to connect

-port <String> AD port (uses 389 and 636 by default)

-usessl [<SwitchParameter>] Connect via SSL

-username <String> AD username (eg `admin@domain.com`)

-adpassword <String> AD password

-basedn <String> Base AD DN

-force [<SwitchParameter>] Skip AD tests

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<http://go.microsoft.com/fwlink/?LinkID=113216>).

————— EXAMPLE 1 —————

```
PS C:>new-aldirectory -websession $websession -serveraddress "mydc.domain.com" -Verbose -username "admin@domain.com" -adpassword "MYPASSWORD" -basedn DC=domain,DC=com -name "Mydirectory"
```

————— EXAMPLE 2 —————

```
PS C:>new-aldirectory -websession $websession -serveraddress "mydc.domain.com" -Verbose -usessl -username "admin@domain.com" -adpassword "MYPASSWORD" -basedn DC=domain,DC=com -name "Mydirectory"
```

REMARKS To see the examples, type: "get-help new-aldirectory -examples". For more information, type: "get-help new-aldirectory -detailed". For technical information, type: "get-help new-aldirectory -full".

new-ALicon

NAME new-ALicon

SYNOPSIS Converts and uploads image file to be used as icon

SYNTAX new-ALicon [-websession] <Object> [-iconfile] <Object> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Converts and uploads image file to be used as icon

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-iconfile <Object> Icon filename

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Upload-ALicon -websession \$websession -iconfilename "d:mysweeticon.png"

REMARKS To see the examples, type: "get-help new-ALicon -examples". For more information, type: "get-help new-ALicon -detailed". For technical information, type: "get-help new-ALicon -full".

New-ALImage

NAME New-ALImage

SYNOPSIS Creates new image(template)

SYNTAX New-ALImage [-websession] <Object> [-name] <String> [[-description] <String>] [-connectorid] <String> [-appids] <String[]> [-osrevid] <String> [-platrevid] <String> [[-ElasticLayerMode] <String>] [-diskformat] <String> [[-size] <String>] [[-icon] <String>] [[-syspretype] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates new image(template)

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-name <String> Name of the layer

-description <String> Description of the layer

-connectorid <String> ID of Connector to use

-appids <String[]> IDs of application versions to add to image

-osrevid <String> Operating system layer version ID

-platrevid <String> Platform layer version ID

-ElasticLayerMode <String> Elastic Layer setting for the image. Options "None","Session","Office365","SessionOffice365","Desktop"

-diskformat <String> Disk format of the image

-size <String> Size of layer in GB (default 102400)

-icon <String> Icon ID (default 196608)

-syspretype <String> Syspretype for the Image. Options "None","Offline" (default "None")

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$connector = Get-ALconnector -websession $websession -type "Publish"|where{$_.name -eq "PVS"}
$oss = Get-ALOsLayer -websession $websession|where{$_.name -eq "Windows 10
x64"} $osrevs = get-aloslayer -websession $websession -id $oss.id $osrevid = $os-
revs.Revisions.OsLayerRevisionDetail|where{$_.state -eq "Deployable"}|Sort-Object revision -
Descending|select -First 1 $plats = get-alplatformlayer -websession $websession|where{$_.name -eq
"Windows 10 VDA"} $platrevs = get-alplatformlayerdetail -websession $websession -id $plats.id $platformre-
vid = $platrevs.Revisions.PlatformLayerRevisionDetail|where{$_.state -eq "Deployable"}|Sort-Object revision
-Descending|select -First 1 $ids = @("1081350","1081349") new-alimage -websession $websession -name
"Win10TEST55" -description "Accounting" -connectorid $connector.id -osrevid $osrevid.Id -appids $ids
-platrevid $platformrevid.id -diskformat $connector.ValidDiskFormats.DiskFormat -elasticlayermode Desktop
```

REMARKS To see the examples, type: "get-help New-ALImage -examples". For more information, type: "get-help New-ALImage -detailed". For technical information, type: "get-help New-ALImage -full".

New-ALImageClone

NAME New-ALImageClone

SYNOPSIS Clones an Image

SYNTAX New-ALImageClone [-websession] <Object> [-imageid] <Object> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Clones an Image

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-imageid <Object> id for the image to be cloned

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>\$image = Get-ALImage -websession \$websession | where {\$_.name -eq "Windows 10 Accounting"}

New-ALImageClone -websession \$websession -imageid \$image.Id -Confirm:\$false -OutVariable ALImageClone

REMARKS To see the examples, type: “get-help New-ALImageClone -examples”. For more information, type: “get-help New-ALImageClone -detailed”. For technical information, type: “get-help New-ALImageClone -full”.

New-ALOsLayerRev

NAME New-ALOsLayerRev

SYNOPSIS Creates new OS layer version

SYNTAX New-ALOsLayerRev [-websession] <Object> [-version] <String> [[-description] <String>] [-connectorid] <String> [-osid] <String> [-osrevid] <String> [[-platformrevid] <String>] [-diskformat] <String> [-shareid] <String> [-name] <String> [[-size] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates new OS layer version

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-version <String> Version of the new layer

-description <String> Description of the layer

-connectorid <String> ID of Connector to use

-osid <String> Operating system layer ID

-osrevid <String> OS version layer id to use

-platformrevid <String> Platform version ID if needed

-diskformat <String> Disk format of the image

-shareid <String> ID of file share

-name <String> Name of the PackagingDisk or layer version

-size <String> Size of layer in GB (default 61440)

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

————— EXAMPLE 1 —————

```
PS C:>$fileshare = Get-ALRemoteshare -websession $websession
```

```
$connector = Get-ALconnector -websession $websession -type CreateIwhere{$_name -eq "MYv-  
Center"} $oss = Get-ALOsLayer -websession $websessionIwhere{$_name -eq "Windows 2016  
Standard"} $osrevs = get-aloslayerDetail -websession $websession -id $oss.id $osrevid = $os-  
revs.Revisions.OsLayerRevisionDetailIwhere{$_state -eq "Deployable"}ISort-Object revision -  
DescendingIselect -First 1 new-aloslayerrev -websession $websession -version "2.0" -connectorid $connector.Id  
-osid $oss.id -osrevid $osrevid.id -diskformat $connector.ValidDiskFormats.DiskFormat -shareid $fileshare.id
```

REMARKS To see the examples, type: “get-help New-ALOsLayerRev -examples”. For more information, type: “get-help New-ALOsLayerRev -detailed”. For technical information, type: “get-help New-ALOsLayerRev -full”.

New-ALPlatformLayer

NAME New-ALPlatformLayer

SYNOPSIS Creates new platform layer

SYNTAX New-ALPlatformLayer [-websession] <Object> [[-version] <String>] [-osrevid] <String> [-connectorid] <String> [[-Description] <String>] [-shareid] <String> [[-iconid] <String>] [-name] <String> [[-size] <String>] [-diskformat] <String> [[-platformrevid] <String>] [-type] <String> [[-HypervisorPlatformTypeId] <String>] [[-ProvisioningPlatformTypeId] <String>] [[-BrokerPlatformTypeId] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates new platform layer

PARAMETERS

- websession <Object>** Existing Webrequest session for ELM Appliance
- version <String>** Version of the new layer
- osrevid <String>** OS version layer id to use
- connectorid <String>** ID of Connector to use
- Description <String>** Description of the layer
- shareid <String>** ID of file share
- iconid <String>**
- name <String>** Name of the layer
- size <String>** Size of layer in GB (default 10240)
- diskformat <String>** Disk format of the image
- platformrevid <String>** Platform version ID if needed
- type <String>** Type of platform layer to create (Create or Publish)
- HypervisorPlatformTypeId <String>** Hypervisor type of platform layer (default=vsphere)
- ProvisioningPlatformTypeId <String>** Provisioning type MCS or PVS (default=mcs)

-BrokerPlatformTypeId <String> Broker type used (default=xendesktop)

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$fileshare = Get-ALRemoteshare -websession $websession
```

```
$connector = Get-ALconnector -websession $websession -type CreateIwhere{$_.name -eq "MYv-  
Center"} $oss = Get-ALOsLayer -websession $websessionIwhere{$_.name -eq "Windows 2016  
Standard"} $osrevs = get-aloslayerdetail -websession $websession -id $oss.id $osrevid = $os-  
revs.Revisions.OsLayerRevisionDetailIwhere{$_.state -eq "Deployable"}|Sort-Object revision -  
DescendingIselect -First 1 New-ALPlatformLayer -websession $websession -osrevid $osrevid.Id -  
name "Citrix XA VDA 7.18" -connectorid $connector.id -shareid $fileshare.id -diskformat $connec-  
tor.ValidDiskFormats.DiskFormat -type Create
```

REMARKS To see the examples, type: “get-help New-ALPlatformLayer -examples”. For more information, type: “get-help New-ALPlatformLayer -detailed”. For technical information, type: “get-help New-ALPlatformLayer -full”.

New-ALPlatformLayerRev

NAME New-ALPlatformLayerRev

SYNOPSIS Creates new platform layer version

SYNTAX New-ALPlatformLayerRev [-websession] <Object> [-osrevid] <String> [-connectorid] <String> [[-Description] <String>] [-shareid] <String> [-layerid] <String> [-layerrevid] <String> [-version] <String> [-Diskname] <String> [[-size] <String>] [-diskformat] <String> [[-HypervisorPlatformTypeId] <String>] [[-ProvisioningPlatformTypeId] <String>] [[-BrokerPlatformTypeId] <String>] [-WhatIf] [-Confirm] [<Common-Parameters>]

DESCRIPTION Creates new platform layer version

PARAMETERS

- websession <Object>** Existing Webrequest session for ELM Appliance
- osrevid <String>** OS version layer id to use
- connectorid <String>** ID of Connector to use
- Description <String>** Description of the layer
- shareid <String>** ID of file share
- layerid <String>** Platform layer ID
- layerrevid <String>** Version ID to base version from
- version <String>** Version of the new layer
- Diskname <String>** Disk file name
- size <String>** Size of layer in MB (default 10240)
- diskformat <String>** Disk format of the image
- HypervisorPlatformTypeId <String>** Hypervisor type of platform layer (default=vsphere)
- ProvisioningPlatformTypeId <String>** Provisioning type MCS or PVS (default=mcs)
- BrokerPlatformTypeId <String>** Broker type used (default=xendesktop)

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>\$connector = Get-ALconnector -websession \$websession -type "Create"

```
$shares = get-alremoteshare -websession $websession $oss = Get-ALOsLayer -websession $websession  
$osrevs = get-aloslayerdetail -websession $websession -id $oss.id  
$osrevid = $osrevs.Revisions.OsLayerRevisionDetailwhere{$_state -eq "Deployable"}|Sort-Object revision -  
Descending|select -First 1 $plats = Get-ALPlatformlayer -websession $websessionwhere{$_name -eq "Win-  
dows 10 VDA"} $platrevs = get-alplatformlayerDetail -websession $websession -id $plats.id $platformrevid  
= $platrevs.Revisions.PlatformLayerRevisionDetailwhere{$_state -eq "Deployable"}|Sort-Object revision -  
Descending|select -First 1
```

```
$params = @{ websession = $websession; osrevid = $osrevid.Id; connectorid = $connector.Id; shareid =  
$shares.id; layerid = $plats.Id; layerrevid = $platformrevid.id; version = "5.0"; Diskname = $plats.Name; Ver-  
bose = $true; Description = "test"; diskformat = $connector.ValidDiskFormats.DiskFormat;
```

REMARKS To see the examples, type: "get-help New-ALPlatformLayerRev -examples". For more information, type: "get-help New-ALPlatformLayerRev -detailed". For technical information, type: "get-help New-ALPlatformLayerRev -full".

new-ALVcenterConnector

NAME new-ALVcenterConnector

SYNOPSIS Creates vCenter Connector configuration

SYNTAX new-ALVcenterConnector [-websession] <Object> [-name] <Object> [-dc] <Object> [-datastore] <Object> [-hostsystem] <Object> [-network] <Object> [-folder] <Object> [-connid] <Object> [-vcenterpass] <Object> [-username] <Object> [-vcenter] <Object> [[-vmtemplate] <Object>] [[-cachesize] <Object>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Creates vCenter Connector configuration

PARAMETERS

- websession <Object>** Existing Webrequest session for ELM Appliance
- name <Object>** Name of the new connector
- dc <Object>** vCenter Datacenter id
- datastore <Object>** vCenter Datastore id
- hostsystem <Object>** vCenter ESXI hostname id
- network <Object>** vCenter network id
- folder <Object>** vCenter folder id
- connid <Object>** ELM platform connection id
- vcenterpass <Object>** vCenter password to authenticate
- username <Object>** vCenter username to authenticate
- vcenter <Object>** vCenter hostname
- vmtemplate <Object>** vCenter template id to use
- cachesize <Object>** Cache size for connector (GB)
- WhatIf [<SwitchParameter>]**
- Confirm [<SwitchParameter>]**

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$Params = @{
Name = "MyconnectorTest" DC = $dc DATASTORE = $datastore HOSTSYSTEM = $hostvar NETWORK =
$network FOLDER = $folder CONNID = $type.Id VMTEMPLATE = $template CACHESIZE = "250" }
new-AIVcenterConnector -websession $websession -username $usernamevc -vcenter $vcentername -
vcenterpass $vcenterpassword @params
```

REMARKS To see the examples, type: “get-help new-AIVcenterConnector -examples”. For more information, type: “get-help new-AIVcenterConnector -detailed”. For technical information, type: “get-help new-AIVcenterConnector -full”.

Commands

This page contains details on *** commands.

Remove-ALAppassignment

NAME Remove-ALAppassignment

SYNOPSIS Removes a layer(application) assignment to image(template)

SYNTAX Remove-ALAppassignment [-websession] <Object> [-applayerid] <String> [-imageid] <String> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes a layer(application) assignment to image(template)

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-applayerid <String>

-imageid <String> Image or template where application should be removed

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$image = Get-ALImage -websession $websession|where{$_name -eq "Accounting"}
```

```
$app = Get-ALapplayer -websession $websession|where{$_name -eq "Libre Office"}
$apprevs = get-alapplayer -websession $websession -id $app.Id $apprevid = $apprevs.Revisions.AppLayerRevisionDetail|where{$_state -eq "Deployable"}|Sort-Object revision -Descending|select -First 1
remove-alappassignment -websession $websession -applayerid $apprevid.LayerId -imageid $image.id
```

REMARKS To see the examples, type: “get-help Remove-ALAppassignment -examples”. For more information, type: “get-help Remove-ALAppassignment -detailed”. For technical information, type: “get-help Remove-ALAppassignment -full”.

Remove-ALAppLayerRev

NAME Remove-ALAppLayerRev

SYNOPSIS Removes a app layer version

SYNTAX Remove-ALAppLayerRev [-websession] <Object> [-appid] <Object> [-apprev] <Object> [-fileshareid] <Object> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes a app layer version

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-appid <Object> Base application layer version id to use

-apprev <Object> Application revision version id to use

-fileshareid <Object>

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$fileshare = Get-ALRemoteshare -websession $websession
```

```
$appid = Get-ALaplayer -websession $websession | where{$_.name -eq "7-Zip"} $apprev = get-alaplayerDetail -websession $websession -id $appid.Id $apprev = $apprev.Revisions.AppLayerRevisionDetail | where{$_.candelete -eq $true} | Sort-Object revision -Descending | select -First 1 remove-alaplayerrev -websession $websession -appid $appid.Id -apprev $apprev.id -fileshareid $fileshare.id
```

REMARKS To see the examples, type: “get-help Remove-ALAppLayerRev -examples”. For more information, type: “get-help Remove-ALAppLayerRev -detailed”. For technical information, type: “get-help Remove-ALAppLayerRev -full”.

Remove-ALConnector

NAME Remove-ALConnector

SYNOPSIS Removes Connector

SYNTAX Remove-ALConnector [-websession] <Object> [-connid] <Object> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes Connector

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-connid <Object> Connector ID

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Remove-ALConnector -websession \$websession -connid \$conn.Id

REMARKS To see the examples, type: “get-help Remove-ALConnector -examples”. For more information, type: “get-help Remove-ALConnector -detailed”. For technical information, type: “get-help Remove-ALConnector -full”.

remove-ALDirectory

NAME remove-ALDirectory

SYNOPSIS Removes Directory Junction

SYNTAX remove-ALDirectory [-websession] <Object> [-id] <String> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes Directory Junction

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> Directory Junction ID

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Remove-ALDirectory -websession \$websession -id "4915204"

REMARKS To see the examples, type: "get-help remove-ALDirectory -examples". For more information, type: "get-help remove-ALDirectory -detailed". For technical information, type: "get-help remove-ALDirectory -full".

Remove-ALELAppassignment

NAME Remove-ALELAppassignment

SYNOPSIS Removes a user account or group to an applications elastic layer assignment

SYNTAX Remove-ALELAppassignment [-websession] <Object> [-applayerid] <String> [-user] <String> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes a user account or group to an applications elastic layer assignment

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-applayerid <String>

-user <String> LDAP located user object

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(http://go.microsoft.com/fwlink/?LinkID=113216\)](http://go.microsoft.com/fwlink/?LinkID=113216).

EXAMPLE 1

```
PS C:>$user = get-alldapobject -websession $websession -object "myusername"
remove-alelappassignment -websession $websession -apprevId $apprevId.Id -user $user
```

EXAMPLE 2

```
PS C:>$users = @(‘MyGroup1’,‘MyGroup2’,‘Domain Users’)
$finduser = $users|get-alldapobject -websession $websession $app = Get-ALaplayerDetail -websession $websession|where{$_name -eq ‘Libre Office’} $apprevs = Get-ALaplayerDetail -websession $websession -id $app.Id $apprevId = $apprevs.Revisions.AppLayerRevisionDetail|where{$_state -eq ‘Deployable’}|Sort-Object revision -Descending|select -First 1 $finduser|remove-alelappassignment -websession $websession -apprevId $apprevId.Id
```

REMARKS To see the examples, type: “get-help Remove-ALELAppassignment -examples”. For more information, type: “get-help Remove-ALELAppassignment -detailed”. For technical information, type: “get-help Remove-ALELAppassignment -full”.

remove-ALicon

NAME remove-ALicon

SYNOPSIS Removes icon based on ID

SYNTAX remove-ALicon [-websession] <Object> [-iconid] <String> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes icon based on ID

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-iconid <String> Icon ID

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Remove-ALicon -websession \$websession -iconid "4259847"

REMARKS To see the examples, type: "get-help remove-ALicon -examples". For more information, type: "get-help remove-ALicon -detailed". For technical information, type: "get-help remove-ALicon -full".

Remove-ALImage

NAME Remove-ALImage

SYNOPSIS Removes image(template)

SYNTAX Remove-ALImage [-websession] <Object> [-id] <String> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes image(template)

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> ID of image to remove

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$image = Get-ALImage -websession $websession|where{ $_.name -eq "Windows 10 Accounting"}
```

```
Remove-ALImage -websession $websession -imageid $image.id
```

REMARKS To see the examples, type: “get-help Remove-ALImage -examples”. For more information, type: “get-help Remove-ALImage -detailed”. For technical information, type: “get-help Remove-ALImage -full”.

Remove-ALOSLayerRev

NAME Remove-ALOSLayerRev

SYNOPSIS Removes a OS layer version

SYNTAX Remove-ALOSLayerRev [-websession] <Object> [-osid] <Object> [-osrevid] <Object> [-fileshareid] <Object> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes a OS layer version

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-osid <Object> Base OS layer version id to use

-osrevid <Object> OS revision version id to use

-fileshareid <Object>

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>\$fileshare = Get-ALRemoteshare -websession \$websession

```
$osid = Get-ALOSlayer -websession $websession | where{$_name -eq "Windows 10 x64"} $osrevid = Get-ALOSlayerDetail -websession $websession -id $osid.Id $osrevid = $osrevid.Revisions.OSLayerRevisionDetail | where{$_candelete -eq $true} | Sort-Object revision -Descending | select -Last 1 remove-aloslayerrev -websession $websession -osid $osid.Id -osrevid $osrevid.id -fileshareid $fileshare.id
```

REMARKS To see the examples, type: “get-help Remove-ALOSLayerRev -examples”. For more information, type: “get-help Remove-ALOSLayerRev -detailed”. For technical information, type: “get-help Remove-ALOSLayerRev -full”.

Remove-ALPlatformLayerRev

NAME Remove-ALPlatformLayerRev

SYNOPSIS Removes a platform layer version

SYNTAX Remove-ALPlatformLayerRev [-websession] <Object> [-platformid] <Object> [-platformrevid] <Object> [-fileshareid] <Object> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Removes a platform layer version

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-platformid <Object> Base platform layer version id to use

-platformrevid <Object> Platform revision version id to use

-fileshareid <Object>

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$fileshare = Get-ALRemoteshare -websession $websession
```

```
$platformid = Get-ALPlatformlayer -websession $websession | where{$_.name -eq "Windows 10 VDA"}
$platformrevid = Get-ALPlatformlayerDetail -websession $websession -id $platformid.Id $platformrevid =
$platformrevid.Revisions.PlatformLayerRevisionDetail | where{$_.candelete -eq $true} | Sort-Object revision
-Descending | select -First 1 remove-alplatformlayerrev -websession $websession -platformid $platformid.Id
-platformrevid $platformrevid.id -fileshareid $fileshare.id
```

REMARKS To see the examples, type: “get-help Remove-ALPlatformLayerRev -examples”. For more information, type: “get-help Remove-ALPlatformLayerRev -detailed”. For technical information, type: “get-help Remove-ALPlatformLayerRev -full”.

Commands

This page contains details on *** commands.

Set-ALAdminUser

NAME Set-ALAdminUser

SYNOPSIS Sets Administrator User Password

SYNTAX Set-ALAdminUser [-websession] <Object> [[-Password] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Sets Administrator User Password

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-Password <String> New Password for the User

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Set-ALAdminUser -websession \$websession -Password \$PlainPassword -Verbose

REMARKS To see the examples, type: “get-help Set-ALAdminUser -examples”. For more information, type: “get-help Set-ALAdminUser -detailed”. For technical information, type: “get-help Set-ALAdminUser -full”.

Set-ALAppplayer

NAME Set-ALAppplayer

SYNOPSIS Edits values of an application layer

SYNTAX Set-ALAppplayer [-websession] <Object> [-id] <String> [[-name] <String>] [[-description] <String>] [[-scriptpath] <String>] [[-icon] <String>] [[-OsLayerSwitching] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Edits values of an application layer

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> ID of the applayer to edit

-name <String> Name of the application layer

-description <String> Description of the layer

-scriptpath <String> Path of script to be run

-icon <String> Icon ID

-OsLayerSwitching <String> Allow OS Switching NotBoundToOsLayer=ON BoundToOsLayer=OFF

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$app = Get-ALAppplayer -websession $websession|where{$_.name -eq "7-Zip"}
```

```
Set-alappplayer -websession $websession -name "7-Zip" -description "7-zip" -id $app.Id -scriptpath "C:NeededScript.ps1" -OsLayerSwitching BoundToOsLayer
```

REMARKS To see the examples, type: “get-help Set-ALApplayer -examples”. For more information, type: “get-help Set-ALApplayer -detailed”. For technical information, type: “get-help Set-ALApplayer -full”.

Set-ALApplayerRev

NAME Set-ALApplayerRev

SYNOPSIS Edits values of an application layer version

SYNTAX Set-ALApplayerRev [-websession] <Object> [-layerid] <String> [-revid] <String> [[-name] <String>] [[-description] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Edits values of an application layer version

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-layerid <String> ID of the applayer to edit

-revid <String> ID of the applayer version to edit

-name <String> Name of the application layer version

-description <String> Description of the layer version

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$app = Get-ALApplayer -websession $websession|where{$_name -eq "7-Zip"}
```

```
$appdetail = Get-ALApplayerDetail -websession $websession -id $app.Id $appver = $appdetail.Revisions.AppLayerRevisionDetail | select-object -last 1 Set-ALApplayerRev -websession $websession -layerid $app.Id -revid $appver.Id -name "21.06" -description "7-zip 21.06 (2021-11-24)"
```

REMARKS To see the examples, type: “get-help Set-ALApplayerRev -examples”. For more information, type: “get-help Set-ALApplayerRev -detailed”. For technical information, type: “get-help Set-ALApplayerRev -full”.

Set-ALConnectorCred

NAME Set-ALConnectorCred

SYNOPSIS Sets Connector Credentials

SYNTAX Set-ALConnectorCred [-websession] <Object> [-username] <String> [-password] <String> [-config] <PSObject> [-connector] <PSObject> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Sets Connector Username and Pass

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-username <String> Username to be used for Connector

-password <String> password to be used for Connector

-config <PSObject> Configuration settings for specific connector (Use get-alconnectordetail)

-connector <PSObject> Configurations for specific connector (Use get-alconnector)

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Set-ALconnectorCred -websession $websession -config $ConnectorConfig -connector $connector -
username "domainfirst.last" -password "Test123"
```

REMARKS To see the examples, type: “get-help Set-ALConnectorCred -examples”. For more information, type: “get-help Set-ALConnectorCred -detailed”. For technical information, type: “get-help Set-ALConnectorCred -full”.

set-aldirectory

NAME set-aldirectory

SYNOPSIS Sets properties of an existing Directory Junction

SYNTAX set-aldirectory [-websession] <Object> [-id] <Object> [[-name] <String>] [[-serveraddress] <String>] [[-port] <String>] [[-usessl] <String>] [[-username] <String>] [-adpassword] <String> [-force] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Sets properties of an existing Directory Junction

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <Object> Junction ID

-name <String> Junction name

-serveraddress <String> AD server to connect

-port <String> AD port (uses 389 and 636 by default)

-usessl <String> Connect via SSL

-username <String> AD username (eg `admin@domain.com`)

-adpassword <String> AD password

-force [<SwitchParameter>] Skip AD tests

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>Set-aldirectory -websession \$websession -adpassword "MYPASSWORD" -id \$directory.id

————— EXAMPLE 2 —————

```
PS C:>Set-aldirectory -websession $websession -adpassword "MYPASSWORD" -id $directory.id -name  
"MYNEWNAME"
```

REMARKS To see the examples, type: “get-help set-aldirectory -examples”. For more information, type: “get-help set-aldirectory -detailed”. For technical information, type: “get-help set-aldirectory -full”.

Set-ALImage

NAME Set-ALImage

SYNOPSIS Edits values of a image(template)

SYNTAX Set-ALImage [-websession] <Object> [-id] <String> [[-name] <String> [[-description] <String> [[-connectorid] <String>] [[-osrevid] <String>] [[-platrevid] <String>] [[-applayerid] <Array>] [[-apprevid] <Array>] [[-ElasticLayerMode] <String>] [[-diskformat] <String>] [[-size] <String>] [[-icon] <String>] [[-syspreptype] <String>] [[-LayeredImageDiskFilename] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Edits values of a image(template)

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> ID of image

-name <String> Name of the image

-description <String> Description of the image

-connectorid <String> ID of Connector to use

-osrevid <String> Operating system layer version ID

-platrevid <String> Platform layer version ID

-applayerid <Array> Application layer ID

-apprevid <Array> Application layer version ID

-ElasticLayerMode <String> Elastic Layer setting for the image. Options
"None","Session","Office365","SessionOffice365","Desktop"

-diskformat <String> Disk format of the image

-size <String> Size of layer in MB

-icon <String> Icon ID

-syspreptype <String> Syspreptype for the Image. Options “None”, “Offline”

-LayeredImageDiskFilename <String>

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>\$fileshare = Get-ALRemoteshare -websession \$websession

```
$connector = Get-ALconnector -websession $websession -type CreateIwhere{$_name -eq "MYV-
Center"} $oss = Get-ALOsLayer -websession $websessionIwhere{$_name -eq "Windows 10
x64"} $osrevs = get-aloslayerdetail -websession $websession -id $oss.id $osrevid = $os-
revs.Revisions.OsLayerRevisionDetailIwhere{$_state -eq "Deployable"}|Sort-Object revision -
DescendingIselect -First 1 $plats = Get-ALPlatformlayer -websession $websessionIwhere{$_name -eq
"Windows 10 VDA"} $platrevs = get-alplatformlayerdetail -websession $websession -id $plats.id $platformrev-
vid = $platrevs.Revisions.PlatformLayerRevisionDetailIwhere{$_state -eq "Deployable"}|Sort-Object revision
-DescendingIselect -First 1 $image = Get-ALImage -websession $websessionIwhere{$_name -eq "Windows 10
Accounting"} Set-alimage -websession $websession -name $images.Name -description "My new description"
-connectorid $connector.id -osrevid $osrevid.Id -platrevid $platformrevid.id -id $image.Id -ElasticLayerMode
Session -diskformat $connector.ValidDiskFormats.DiskFormat -syspreptype Offline
```

```
### Edit image with latest revision for a specific app or apps *** $apps = @("Winscp","7-zip") $applay-
erids = foreach ($app in $apps){Get-ALapplayer -websession $websessionIwhere{$_name -eq $app}} $ap-
prevs = foreach ($applayerid in $applayerids){get-alapplayerDetail -websession $websession -id $applay-
erid.Id} $apprevid = foreach ($apprev in $apprevs){$apprev.Revisions.AppLayerRevisionDetailIwhere{$_state
-eq "Deployable"}|Sort-Object DisplayedVersion -DescendingIselect -First 1} Set-alimage -websession $web-
session -name $images.Name -description "My new description" -connectorid $connector.id -osrevid
$osrevid.Id -platrevid $platformrevid.id -id $image.Id -ElasticLayerMode Session -diskformat $connec-
tor.ValidDiskFormats.DiskFormat -applayerid $apprevid.LayerId -apprevid $apprevid.Id -syspreptype Offline
```

REMARKS To see the examples, type: “get-help Set-ALImage -examples”. For more information, type: “get-help Set-ALImage -detailed”. For technical information, type: “get-help Set-ALImage -full”.

Set-ALPlatformlayer

NAME Set-ALPlatformlayer

SYNOPSIS Edits values of an platform layer

SYNTAX Set-ALPlatformlayer [-websession] <Object> [-id] <String> [[-name] <String>] [[-description] <String>] [[-scriptpath] <String>] [[-icon] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Edits values of an platform layer

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String> ID of the platformlayer to edit

-name <String> Name of the platform layer

-description <String> Description of the layer

-scriptpath <String> Path of script to be run

-icon <String> Icon ID

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>$platform = Get-ALplatformlayer -websession $websession|where{$_ .name -eq "XenDesktop"}
```

```
Set-ALPlatformlayer -websession $websession -name "XenDesktop" -description "Xendesktop-Layer" -id $platform.Id -scriptpath "C:NeededScript.ps1"
```

REMARKS To see the examples, type: “get-help Set-ALPlatformlayer -examples”. For more information, type: “get-help Set-ALPlatformlayer -detailed”. For technical information, type: “get-help Set-ALPlatformlayer -full”.

Set-alVcenterConnector

NAME Set-alVcenterConnector

SYNOPSIS Sets Vcenter Connector configuration

SYNTAX Set-alVcenterConnector [-websession] <Object> [-config] <Object> [-force] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Sets Vcenter Connector configuration

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-config <Object> Connector Config

-force [<SwitchParameter>] Skip Verify

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Set-VcenterConnector -websession $websession -config $connectorconfig
```

REMARKS To see the examples, type: “get-help Set-alVcenterConnector -examples”. For more information, type: “get-help Set-alVcenterConnector -detailed”. For technical information, type: “get-help Set-alVcenterConnector -full”.

Commands

This page contains details on *** commands.

Stop-ALWorkTicket

NAME Stop-ALWorkTicket

SYNOPSIS Stops or cancels a running layer operation process

SYNTAX Stop-ALWorkTicket [-websession] <Object> [-id] <String> [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION Stops or cancels a running layer operation process

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-id <String>

-WhatIf [<SwitchParameter>]

-Confirm [<SwitchParameter>]

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>Stop-ALWorkTicket -websession $websession
```

REMARKS To see the examples, type: “get-help Stop-ALWorkTicket -examples”. For more information, type: “get-help Stop-ALWorkTicket -detailed”. For technical information, type: “get-help Stop-ALWorkTicket -full”.

Commands

This page contains details on *** commands.

CHAPTER 78

test-aldirectory

NAME test-aldirectory

SYNOPSIS Test Directory Junction connectivity

SYNTAX test-aldirectory [-websession] <Object> [-serveraddress] <String> [[-port] <String>] [-usessl] [<CommonParameters>]

DESCRIPTION Test Directory Junction connectivity

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-serveraddress <String> AD server to connect

-port <String> AD port (uses 389 and 636 by default)

-usessl [<SwitchParameter>] Connect via SSL

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

PS C:>test-aldirectory -websession \$websession -serveraddress "mydc.domain.com" -Verbose

EXAMPLE 2

PS C:>test-aldirectory -websession \$websession -serveraddress "mydc.domain.com" -Verbose -usessl

REMARKS To see the examples, type: "get-help test-aldirectory -examples". For more information, type: "get-help test-aldirectory -detailed". For technical information, type: "get-help test-aldirectory -full".

test-aldirectoryauth

NAME test-aldirectoryauth

SYNOPSIS Test Directory Junction authentication

SYNTAX test-aldirectoryauth [-websession] <Object> [-serveraddress] <String> [[-port] <String>] [-usessl] [-username] <String> [-adpassword] <String> [<CommonParameters>]

DESCRIPTION Test Directory Junction authentication

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-serveraddress <String> AD server to connect

-port <String> AD port (uses 389 and 636 by default)

-usessl [<SwitchParameter>] Connect via SSL

-username <String> AD username (eg `admin@domain.com`)

-adpassword <String> AD password

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>test-aldirectoryauth -websession $websession -serveraddress "mydc.domain.com" -Verbose -username "admin@domain.com" -adpassword "MYPASSWORD"
```

EXAMPLE 2

```
PS C:>test-aldirectoryauth -websession $websession -serveraddress "mydc.domain.com" -Verbose -usessl -username "admin@domain.com" -adpassword "MYPASSWORD"
```

REMARKS To see the examples, type: “get-help test-aldirectoryauth -examples”. For more information, type: “get-help test-aldirectoryauth -detailed”. For technical information, type: “get-help test-aldirectoryauth -full”.

test-aldirectorydn

NAME test-aldirectorydn

SYNOPSIS Test Directory Junction DN path

SYNTAX test-aldirectorydn [-websession] <Object> [-serveraddress] <String> [[-port] <String>] [-usessl] [-username] <String> [-adpassword] <String> [-basedn] <String> [<CommonParameters>]

DESCRIPTION Test Directory Junction DN path

PARAMETERS

-websession <Object> Existing Webrequest session for ELM Appliance

-serveraddress <String> AD server to connect

-port <String> AD port (uses 389 and 636 by default)

-usessl [<SwitchParameter>] Connect via SSL

-username <String> AD username (eg `admin@domain.com`)

-adpassword <String> AD password

-basedn <String> Base AD DN

<CommonParameters> This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<http://go.microsoft.com/fwlink/?LinkID=113216>).

EXAMPLE 1

```
PS C:>test-aldirectorydn -websession $websession -serveraddress "mydc.domain.com" -Verbose -username "admin@domain.com" -adpassword "MYPASSWORD" -basedn DC=domain,DC=com
```

EXAMPLE 2

```
PS C:>test-aldirectorydn -websession $websession -serveraddress "mydc.domain.com" -Verbose -usessl -username "admin@domain.com" -adpassword "MYPASSWORD" -basedn DC=domain,DC=com
```

REMARKS To see the examples, type: “get-help test-aldirectorydn -examples”. For more information, type: “get-help test-aldirectorydn -detailed”. For technical information, type: “get-help test-aldirectorydn -full”.

Application Assignments

81.1 Add app layers to an image

```
$image = Get-ALimage -websession $websession|where{$_ .name -eq "Accounting"}
$app = Get-ALaplayer -websession $websession|where{$_ .name -eq "Libre Office"}
$apprevs = get-alaplayerDetail -websession $websession -id $app.Id
$apprevid = $apprevs.Revisions.AppLayerRevisionDetail|where{$_ .state -eq "Deployable"}
↪|Sort-Object DisplayedVersion -Descending|select -First 1
add-alappassignment -websession $websession -apprevid $apprevid.id -imageid $image.id
```

81.2 Remove app layers from an image

```
$image = Get-ALimage -websession $websession|where{$_ .name -eq "Accounting"}
$app = Get-ALaplayer -websession $websession|where{$_ .name -eq "Libre Office"}
$apprevs = Get-ALaplayerDetail -websession $websession -id $app.Id
$apprevid = $apprevs.Revisions.AppLayerRevisionDetail|where{$_ .state -eq "Deployable"}
↪|Sort-Object DisplayedVersion -Descending|select -First 1
remove-alappassignment -websession $websession -aplayerid $apprevid.LayerId -imageid
↪$image.id
```

81.3 Add user\group to Elastic Layers

```
$users = @('MyGroup1','MyGroup2','Domain Users')
$finduser = $users|get-alldapobject -websession $websession
$app = Get-ALaplayer -websession $websession|where{$_ .name -eq "Libre Office"}
$apprevs = Get-ALaplayerDetail -websession $websession -id $app.Id
$apprevid = $apprevs.Revisions.AppLayerRevisionDetail|where{$_ .state -eq "Deployable"}
↪|Sort-Object DisplayedVersion -Descending|select -First 1
$add = $finduser|add-alelappassignment -websession $websession -apprevid $apprevid.Id
```

81.4 Remove user\group from Elastic Layers

```
$users = @('MyGroup1','MyGroup2','Domain Users')
$finduser = $users|get-alldapobject -websession $websession
$app = Get-ALapplayer -websession $websession|where{$_ .name -eq "Libre Office"}
$apprevs = Get-ALapplayerDetail -websession $websession -id $app.Id
$apprevid = $apprevs.Revisions.AppLayerRevisionDetail|where{$_ .state -eq "Deployable"}
↪|Sort-Object DisplayedVersion -Descending|select -First 1
$finduser|remove-alelappassignment -websession $websession -apprevid $apprevid.Id
```

82.1 New Application Layer

```
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
    ↳ "MYvCenter"}
$fileshare = Get-ALRemoteshare -websession $websession
$oss = Get-ALOsLayer -websession $websession|where{$_ .name -eq "Windows 10 x64"}
$osrevs = get-aloslayerdetail -websession $websession -id $oss.id
$osrevid = $osrevs.Revisions.OsLayerRevisionDetail|where{$_ .state -eq "Deployable"}
    ↳ |Sort-Object DisplayedVersion -Descending|select -First 1
new-alaplayer -websession $websession -version "1.0" -name "Accounting APP" -
    ↳ description "Accounting application" -connectorid $connector.id -osrevid $osrevid.
    ↳ Id -diskformat $connector.ValidDiskFormats.DiskFormat -OsLayerSwitching_
    ↳ BoundToOsLayer -fileshareid $fileshare.id
```

82.2 New Application Layer Version

```
$fileshare = Get-ALRemoteshare -websession $websession
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
    ↳ "MYvCenter"}
$app = Get-ALaplayer -websession $websession|where{$_ .name -eq "7-Zip"}
$oss = Get-ALOsLayer -websession $websession
$osrevs = get-aloslayerdetail -websession $websession -id $app.AssociatedOsLayerId
$osrevid = $osrevs.Revisions.OsLayerRevisionDetail|where{$_ .state -eq "Deployable"}
    ↳ |Sort-Object DisplayedVersion -Descending|select -First 1
$apprevs = get-alaplayerdetail -websession $websession -id $app.Id
$apprevid = $apprevs.Revisions.AppLayerRevisionDetail|where{$_ .state -eq "Deployable"}
    ↳ |Sort-Object DisplayedVersion -Descending|select -First 1
new-alaplayerrev -websession $websession -version "9.0" -name $app.Name -connectorid
    ↳ $connector.id -appid $app.Id -apprevid $apprevid.id -osrevid $osrevid.Id -
    ↳ diskformat $connector.ValidDiskFormats.DiskFormat -fileshareid $fileshare.id
```

82.3 Set Application Layer

```
$app = Get-ALapplayer -websession $websession | where{$_ .name -eq "7-Zip"}
Set-alapplayer -websession $websession -name "7-Zip" -description "7-zip" -id $app.Id -
↳ -scriptpath "C:\NeededScript.ps1" -OsLayerSwitching BoundToOsLayer
```

82.4 Remove Application Layer Revision

```
$fileshare = Get-ALRemoteshare -websession $websession
$appid = Get-ALapplayer -websession $websession | where{$_ .name -eq "7-Zip"}
$apprev = get-alaplayerDetail -websession $websession -id $appid.Id
$apprev = $apprev.Revisions.AppLayerRevisionDetail | where{$_ .candelete -eq $true}
↳ | Sort-Object DisplayedVersion -Descending | select -First 1
remove-alaplayerrev -websession $websession -appid $appid.Id -apprev $apprev.id -
↳ fileshareid $fileshare.id
```

Connect and Disconnect

83.1 Connect

```
$aplip = "192.168.1.5"
$pass = "Password"
$username = "administrator"
$SecurePassword = ConvertTo-SecureString $Pass -AsPlainText -Force
$Credential = New-Object System.Management.Automation.PSCredential ($Username,
    ↪$SecurePassword)
$websession = Connect-alsession -aplip $aplip -Credential $Credential -Verbose
```

83.2 Disconnect

```
disconnect-alsession -websession $websession
```


84.1 General

84.1.1 Get Connector Detail

```
$conn = get-alconnector -websession $websession -type Publish -name "MyconnectorTest7"
get-alconnectordetail -websession $websession -connid $conn.Id -port $conn.
↪ConfigurationSslPort
```

84.1.2 Remove Connector

```
$conn = get-alconnector -websession $websession -type Publish -name "MyconnectorTest7"
Remove-ALConnector -websession $websession -connid $conn.Id -Confirm:$false
```

84.1.3 Set Connector Credentials

```
$conn = get-alconnector -websession $websession -type Publish -name "MyconnectorTest7"
$conndetail = get-alconnectordetail -websession $websession -connid $conn.Id -port
↪$conn.ConfigurationSslPort
Set-ALconnectorCred -websession $websession -config $conndetail -connector $conn -
↪username "domain\first.last" -password "Test123"
```

84.2 vCenter

84.2.1 Get vCenter connector(s) information

```
Get-alVcenterConnector -websession $websession
```

84.2.2 Get vCenter Resource Info

```
$vcenter = Get-alVcenterConnector -websession $websession
$dc = get-alvcenterobject -websession $websession -configid $vcenter.pccId -username
↳ $vcenter.pccConfig.userName -vcenter $vcenter.pccConfig.vCenterServer -type_
↳ datacenter -configid $vcenter.pccId
$folder
$hostvar = get-alvcenterobject -websession $websession -configid $vcenter.pccId -
↳ username $vcenter.pccConfig.userName -vcenter $vcenter.pccConfig.vCenterServer -
↳ type Host -dc $dc.value
$datastore = get-alvcenterobject -websession $websession -configid $vcenter.pccId -
↳ username $vcenter.pccConfig.userName -vcenter $vcenter.pccConfig.vCenterServer -
↳ type Datastore -dc $dc.value
$network = get-alvcenterobject -websession $websession -configid $vcenter.pccId -
↳ username $vcenter.pccConfig.userName -vcenter $vcenter.pccConfig.vCenterServer -
↳ type network -dc $dc.value
$template = get-alvcenterobject -websession $websession -configid $vcenter.pccId -
↳ username $vcenter.pccConfig.userName -vcenter $vcenter.pccConfig.vCenterServer -
↳ type vmTemplate -vmfolder $dc.vmFolder
$folder = get-alvcenterobject -websession $websession -configid $vcenter.pccId -
↳ username $vcenter.pccConfig.userName -vcenter $vcenter.pccConfig.vCenterServer -
↳ type vmfolder -vmfolder $dc.vmFolder
```

84.2.3 Validate and Set vCenter Password

```
$vcenter = Get-alVcenterConnector -websession $websession
$vcenter.pccConfig|Add-Member -NotePropertyName "password" -NotePropertyValue
↳ "mysecretpassword"

Set-alVcenterConnector -websession $websession -config $vcenter
```

84.2.4 Create vCenter Connector

```
$vcenterpassword = "mysupersecretpassword"
$usernamevc = "domain\username"
$vcentername = "myvcenter.domain.local"
$type = get-alconnectortype -websession $websession -name "Citrix MCS for vSphere"
$dc = get-alvcenterobject -websession $websession -username $usernamevc -vcenter
↳ $vcentername -vcenterpass $vcenterpassword -type Datacenter -name "Lab"
$hostvar = get-alvcenterobject -websession $websession -username $usernamevc -vcenter
↳ $vcentername -vcenterpass $vcenterpassword -type Host -dc $dc.value -name
↳ "myhostname"
$datastore = get-alvcenterobject -websession $websession -username $usernamevc -
↳ vcenter $vcentername -vcenterpass $vcenterpassword -type Datastore -dc $dc.value -
↳ name "nydatastore"
```

(continues on next page)

(continued from previous page)

```
$network = get-alvcenterobject -websession $websession -username $usernamevc -vcenter
↳$vcentername -vcenterpass $vcenterpassword -type network -dc $dc.value -name "VLAN10
↳"
$template = get-alvcenterobject -websession $websession -username $usernamevc -
↳vcenter $vcentername -vcenterpass $vcenterpassword -type vmTemplate -vmfolder $dc.
↳vmFolder -name "CALTEMP"
$folder = get-alvcenterobject -websession $websession -username $usernamevc -vcenter
↳$vcentername -vcenterpass $vcenterpassword -type vmfolder -vmfolder $dc.vmFolder -
↳name "Unidesk"

$params = @{
    Name = "MyconnectorTest"
    DC = $dc
    DATASTORE = $datastore
    HOSTSYSTEM = $hostvar
    NETWORK = $network
    FOLDER = $folder
    CONNID = $type.Id
    VMTEMPLATE = $template
    CACHESIZE = "250"
}

new-AlVcenterConnector -websession $websession -username $usernamevc -vcenter
↳$vcentername -vcenterpass $vcenterpassword @params
```


CHAPTER 85

Directory Junction

85.1 New Directory Junction

```
new-aldirectory -websession $websession -serveraddress "mydc.domain.com" -usessl -  
↪username "admin@domain.com" -adpassword "MYPASSWORD" -basedn DC=domain,DC=com -name  
↪"Mydirectory"
```

85.2 Get ALL Directory Junctions

```
Get-ALDirectory -websession $websession
```

85.3 Get Directory Junction Info

```
get-aldirectorydetail -websession $websession -id $directory.id
```

85.4 Set Directory Junction Info

```
Set-aldirectory -websession $websession -adpassword "MYPASSWORD" -id $directory.id -  
↪name "MYNEWNAME"
```

85.5 Delete Directory Junction

```
Remove-ALDirectory -websession $websession -id "4915204"
```

85.6 User Info

```
$dir = Get-ALDirectory -websession $websession | where{$_ .name -eq "MyDirectory"}
$userid = Get-ALUserList -websession $websession -junctionid $dir.id -dn "CN=Users,
↳DC=mydomain,DC=com" | Where-Object {$_ .loginname -eq "myusername"}
$userdetail = Get-ALUserDetail -websession $websession -junctionid $dir.id -ldapguid
↳$userid.DirectoryId.LdapGuid -dn $userid.DirectoryId.LdapDN -id $userid.DirectoryId.
↳UnideskId
$groups = Get-ALUserGroupMembership -websession $websession -junctionid $dir.id -id
↳$User.DirectoryId.UnideskId -ldapguid $user.FullId.LdapGuid -ldapdn $user.FullId.
↳LdapDN -sid $userdetail.FullId.sid
#build group array for search
$groupids = @()
$groups | %{ $groupids += $_.DirectoryId.UnideskId }
#add user to group array
$groupids += $User.DirectoryId.UnideskId
$app = Get-ALUserAssignment -websession $websession -id $userid.DirectoryId.
↳UnideskId -Verbose
$app | Select-Object LayerName, CurrentRevision, PendingRevision, AssignedViaDisplayName
```

Export and Import Layers

Gets “Exportable” Layers

```
$mypath = "\\mynas\layershare\  
Get-ALExportableRev -websession $websession -sharepath $mypath
```

Gets “Exportable” layers including ones that are already present

```
$mypath = "\\mynas\layershare\  
Get-ALExportableRev -websession $websession -sharepath $mypath -showall
```

Gets “Importable” Layers

```
$mypath = "\\mynas\layershare\  
Get-ALImportableRev -websession $websession -sharepath $mypath
```

Gets “Importable” layers including ones that are already present

```
$mypath = "\\mynas\layershare\  
Get-ALImportableRev -websession $websession -sharepath $mypath -showall
```

86.1 Export Layers

Exports all “exportable” layers to fileshare

```
$mypath = "\\mynas\layershare\  
Get-ALExportableRev -websession $websession -sharepath $mypath | Export-ALLayerrev -  
↪websession $websession -sharepath $mypath
```

Exports all “exportable” layers to fileshare with authentication. (Press CTRL key to select more than one layer)

```
$mypath = "\\mynas\layershare\  
$myusername = "mydomain@domain.com"  
$sharepw = "mysupersecret"  
Get-ALExportableRev -websession $websession -sharepath $mypath -username $myusername -  
→sharepw $sharepw|Export-ALLayerrev -websession $websession -sharepath $mypath -  
→username $myusername -sharepw $sharepw
```

Allows user to select which layers to export. (Press CTRL key to select more than one layer)

```
$mypath = "\\mynas\layershare\  
Get-ALExportableRev -websession $websession -sharepath $mypath|Out-gridview -  
→PassThru|Export-ALLayerrev -websession $websession -sharepath $mypath
```

86.2 Import Layers

Imports all “importable” layers to fileshare

```
$mypath = "\\mynas\layershare\  
Get-ALImportableRev -websession $websession -sharepath $mypath|Import-ALLayerrev -  
→websession $websession -sharepath $mypath
```

Imports all “importable” layers to fileshare with authentication. (Press CTRL key to select more than one layer)

```
$mypath = "\\mynas\layershare\  
$myusername = "mydomain@domain.com"  
$sharepw = "mysupersecret"  
Get-ALImportableRev -websession $websession -sharepath $mypath -username $myusername -  
→sharepw $sharepw|Import-ALLayerrev -websession $websession -sharepath $mypath -  
→username $myusername -sharepw $sharepw
```

Allows user to select which layers to import. (Press CTRL key to select more than one layer)

```
$mypath = "\\mynas\layershare\  
Get-ALImportableRev -websession $websession -sharepath $mypath|Out-gridview -  
→PassThru|Import-ALLayerrev -websession $websession -sharepath $mypath
```


87.1 Get icon ids

```
Get-ALicon -websession $websession
```

87.2 Export all icons (save as png)

```
$icons = Get-ALicon -websession $websession

foreach($icon in $icons)
{
    #No authentication needed to grab image
    Invoke-WebRequest -uri $($icon.url) -OutFile ("D:\Temp\icons\" + $($icon.iconid) +
    ↪ ".png")
}
```

87.3 Get icon associations

```
Get-ALiconassoc -websession $websession -iconid "196608"
```

87.4 Create new icon

```
$iconfile = "D:\Temp\icons\myiconpic.png"
$temp = new-alicon -WebSession $websession -iconfile $iconfile -Verbose
```

87.5 Remove icon

```
Remove-ALicon -websession $websession -iconid "4259840"
```

88.1 Get Image Composition

```
$image = Get-ALImageComp -websession $websession -name "Windows 10 Accounting"
$image.OSLayer
$image.PlatformLayer
$image.AppLayer
```

88.2 Create New Image

```
$fileshare = Get-ALRemoteshare -websession $websession
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
    ↳ "MYvCenter"}
$oss = Get-ALosLayer -websession $websession|where{$_ .name -eq "Windows 10 x64"}
$osrevs = get-aloslayerdetail -websession $websession -id $oss.id
$osrevid = $osrevs.Revisions.OsLayerRevisionDetail|where{$_ .state -eq "Deployable"}
    ↳ |Sort-Object DisplayedVersion -Descending|select -First 1
$plats = get-alplatformlayer -websession $websession|where{$_ .name -eq "Windows 10 VDA
    ↳ "}
$platrevs = get-alplatformlayerdetail -websession $websession -id $plats.id
$platformrevid = $platrevs.Revisions.PlatformLayerRevisionDetail|where{$_ .state -eq
    ↳ "Deployable"}|Sort-Object DisplayedVersion -Descending|select -First 1
#Application IDs
$app = @("Winscp","7-zip")
$appids = @()
foreach ($app in $apps)
{
    $applayerid = Get-ALapplayer -websession $websession|where{$_ .name -eq $app}
    $apprevs = get-alapplayerdetail -websession $websession -id $applayerid.Id
    $apprevid = $apprevs.Revisions.AppLayerRevisionDetail|where{$_ .state -eq
        ↳ "Deployable"}|Sort-Object DisplayedVersion -Descending|select -First 1
```

(continues on next page)

(continued from previous page)

```

    $appids += $apprevId.Id
}
new-alimage -websession $websession -name "Windows 10 Accounting" -description
↪ "Accounting" -connectorid $connector.id -osrevid $osrevid.Id -appids $appids -
↪ platrevid $platformrevid.id -diskformat $connector.ValidDiskFormats.DiskFormat -
↪ ElasticLayerMode Session

```

88.3 Edit Image

```

$filesystem = Get-ALRemoteshare -websession $websession
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
↪ "MYvCenter"}
$oss = Get-ALOsLayer -websession $websession|where{$_ .name -eq "Windows 10 x64"}
$osrevs = get-aloslayerdetail -websession $websession -id $oss.id
$osrevid = $osrevs.Revisions.OsLayerRevisionDetail|where{$_ .state -eq "Deployable"}
↪ |Sort-Object DisplayedVersion -Descending|select -First 1
$plats = Get-ALPlatformlayer -websession $websession|where{$_ .name -eq "Windows 10 VDA
↪ "}
$platrevs = get-alplatformlayerdetail -websession $websession -id $plats.id
$platformrevid = $platrevs.Revisions.PlatformLayerRevisionDetail|where{$_ .state -eq
↪ "Deployable"}|Sort-Object DisplayedVersion -Descending|select -First 1
$image = Get-ALImage -websession $websession|where{$_ .name -eq "Windows 10 Accounting
↪ "}
Set-alimage -websession $websession -name $images.Name -description "My new
↪ description" -connectorid $connector.id -osrevid $osrevid.Id -platrevid
↪ $platformrevid.id -id $image.Id -ElasticLayerMode Session -diskformat $connector.
↪ ValidDiskFormats.DiskFormat

```

88.3.1 Edit image with latest revision for a specific app or apps

```

$app = @("Winscp","7-zip")
$appplayerids = foreach ($app in $apps){Get-ALapplayer -websession $websession|where{$_
↪ .name -eq $app}}
$apprevs = foreach ($appplayerid in $appplayerids){get-alapplayerdetail -websession
↪ $websession -id $appplayerid.Id}
$apprevid = foreach ($apprev in $apprevs){$apprev.Revisions.
↪ AppLayerRevisionDetail|where{$_ .state -eq "Deployable"}|Sort-Object
↪ DisplayedVersion -Descending|select -First 1}
Set-alimage -websession $websession -name $images.Name -description "My new
↪ description" -connectorid $connector.id -osrevid $osrevid.Id -platrevid
↪ $platformrevid.id -id $image.Id -ElasticLayerMode Session -diskformat $connector.
↪ ValidDiskFormats.DiskFormat -applayerid $apprevid.LayerId -apprevid $apprevid.Id

```

88.4 Remove Image

```

$image = Get-ALImage -websession $websession|where{$_ .name -eq "Windows 10 Accounting
↪ "}
Remove-ALImage -websession $websession -imageid $image.id

```

88.5 Publish Image

```
$image = Get-ALImage -websession $websession | where {$_.name -eq "Windows 10 Accounting"
↪}
invoke-alpublish -websession $websession -imageid $image.id
```

88.6 Clone Image

```
$image = Get-ALImage -websession $websession | where {$_.name -eq "Windows 10_
↪Accounting"}
New-ALImageClone -websession $websession -imageid $image.Id -Confirm:$false -
↪OutVariable ALImageClone
```


89.1 Get Local Users

```
Get-ALLocalUser -websession $websession
```

89.2 Set Local Admin Password

```
Set-ALAdminUser -websession $websession -Password $PlainPassword -Verbose
```

Operating System Layers

90.1 Import Operating System

90.1.1 vCenter

```
$fileshare = Get-ALRemoteshare -websession $websession
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
↳ "MYvCenter"}
$shares = get-alremoteshare -websession $websession
#vCenter Command
$vm = Get-VM "Windows2016VM"
$vmid = $vm.Id -replace "VirtualMachine-", ""
$response = import-aloslayer -websession $websession -vmname $vm.name -connectorid
↳ $connector.id -shareid $fileshare.id -name "Windows 2016" -version "1.0" -vmid
↳ $vmid -hypervisor esxi
```

90.1.2 Citrix Hypervisor (XenServer)

Thanks Dan Feller!

```
$fileshare = Get-ALRemoteshare -websession $websession
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
↳ "MYXenServer"}
$shares = get-alremoteshare -websession $websession
#Xen Command
$XenVM = get-xenvm -name $VMName
$response = import-aloslayer -websession $websession -vmname $vmname -connectorid
↳ $connector.id -shareid $fileshare.id -name "Windows 2016" -version "1.0" -vmid
↳ $XenVM.uuid -hypervisor xenserver
```

90.2 New Operating System Layer Version

```
$fileshare = Get-ALRemoteshare -websession $websession
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
↪ "MYvCenter"}
$oss = Get-ALOSlayer -websession $websession|where{$_ .name -eq "Windows 2016 Standard
↪ "}
$osrevs = get-aloslayerDetail -websession $websession -id $oss.id
$osrevid = $osrevs.Revisions.OSLayerRevisionDetail|where{$_ .state -eq "Deployable"}
↪ |Sort-Object DisplayedVersion -Descending|select -First 1
$myosrev = new-aloslayerrev -websession $websession -version "2.0" -connectorid
↪ $connector.Id -osid $oss.id -osrevid $osrevid.id -diskformat $connector.
↪ ValidDiskFormats.DiskFormat -shareid $fileshare.id

#Keep checking for change in task
do{
  $status = get-alstatus -websession $websession -id $myosrev.WorkTicketId
  Start-Sleep -Seconds 5
} Until ($status.state -eq "ActionRequired")
#use function to extract VM NAME from status message
get-almvname -message $status.WorkItems.WorkItemResult.Status
```

90.3 Remove Operating System Layer Revision

```
$fileshare = Get-ALRemoteshare -websession $websession
$osid = Get-ALOSlayer -websession $websession | where{$_ .name -eq "Windows 10 x64"}
$osrevid = Get-ALOSlayerDetail -websession $websession -id $osid.Id
$osrevid = $osrevid.Revisions.OSLayerRevisionDetail | where{$_ .candelete -eq $true} |
↪ Sort-Object DisplayedVersion -Descending | select -Last 1
remove-aloslayerrev -websession $websession -osid $osid.Id -osrevid $osrevid.id -
↪ fileshareid $fileshare.id
```

91.1 New Platform Layer

```
$fileshare = Get-ALRemoteshare -websession $websession
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
↪ "MYvCenter"}
$oss = Get-ALOsLayer -websession $websession|where{$_ .name -eq "Windows 2016 Standard
↪ "}
$osrevs = get-aloslayerdetail -websession $websession -id $oss.id
$osrevid = $osrevs.Revisions.OsLayerRevisionDetail|where{$_ .state -eq "Deployable"}
↪ |Sort-Object DisplayedVersion -Descending|select -First 1
New-ALPlatformLayer -websession $websession -osrevid $osrevid.Id -name "Citrix XA VDA_
↪ 7.18" -connectorid $connector.id -shareid $fileshare.id -diskformat $connector.
↪ ValidDiskFormats.DiskFormat -type Create
```

91.2 New Platform Layer Version

```
$fileshare = Get-ALRemoteshare -websession $websession
$connector = Get-ALconnector -websession $websession -type Create|where{$_ .name -eq
↪ "MYvCenter"}
$oss = Get-ALOsLayer -websession $websession|where{$_ .name -eq "Windows 10 x64"}
$osrevs = get-aloslayerdetail -websession $websession -id $oss.id
$osrevid = $osrevs.Revisions.OsLayerRevisionDetail|where{$_ .state -eq "Deployable"}
↪ |Sort-Object DisplayedVersion -Descending|select -First 1
$plats = Get-ALPlatformlayer -websession $websession|where{$_ .name -eq "Windows 10 VDA
↪ "}
$platrevs = get-alplatformlayerdetail -websession $websession -id $plats.id
$platformrevid = $platrevs.Revisions.PlatformLayerRevisionDetail|where{$_ .state -eq
↪ "Deployable"}|Sort-Object DisplayedVersion -Descending|select -First 1

$params = @{
```

(continues on next page)

(continued from previous page)

```
websession = $websession;
osrevid = $osrevid.Id;
connectorid = $connector.Id;
shareid = $fileshare.id;
layerid = $plats.Id;
layerrevid = $platformrevid.id;
version = "5.0";
Diskname = $plats.Name;
Verbose = $true;
Description = "Citrix VDA 7.18 with windows 10";
diskformat = $connector.ValidDiskFormats.DiskFormat;
}

New-ALPlatformLayerRev @params
```

91.3 Remove Platform Layer Revision

```
$fileshare = Get-ALRemoteshare -websession $websession
$platformid = Get-ALPlatformlayer -websession $websession | where{$_ .name -eq
↪ "Windows 10 VDA"}
$platformrevid = Get-ALPlatformlayerDetail -websession $websession -id $platformid.Id
$platformrevid = $platformrevid.Revisions.PlatformLayerRevisionDetail | where{$_ .
↪ candelete -eq $true} | Sort-Object DisplayedVersion -Descending | select -First 1
remove-alplatformlayerrev -websession $websession -platformid $platformid.Id -
↪ platformrevid $platformrevid.id -fileshareid $fileshare.id
```

92.1 Get System Information (Version)

```
Get-ALSystemInfo -websession $websession
```

92.2 Get System Settings

```
get-alsystemsettinginfo -websession $websession | Select-Object -ExpandProperty value -  
↳Property @{Name="SettingName"; Expression = {$_ .Name}}
```


93.1 Get Task Status

Get all tasks

```
Get-ALStatus -websession $websession
```

Get specific task based on ID (accepts wildcard)

```
Get-ALStatus -id 123456 -websession $websession
```

93.2 Cancel Task

Locate ID of Task `Get-ALStatus -websession $websession`

```
Stop-ALWorkTicket -id 123456 -websession $websession
```